

Technical Data Sheet Creator GLOSS High gloss polyester topcoat

PROPERTIES						
High gloss polyester topcoat Creator GLOSS is applied as the last layer during all the models made by traditional as well as by CNC processing. The product is characterized by easy polishing even after a few days of application and obtains a high gloss (about 80) and perfect smoothness of surface without discoloration. It provides the perfect surface of both the model and the mold made with its.						
RELATED PRODU	стѕ					
Cetox 20 OE		Hardener				
THIN 880 (optional)		Thinner for polyester Spray Filler				
SUBSTRATES						
Creator tooling pastes		Clean of dust				
Creator FPD		dry sand with P320 and degrease.				
Note: Do not apply Creator GLOSS directly onto wash primers, single-pack acrylic products or nitrocellulose products.						
MIXING RATIO						
		Volume ratio	Weight ratio			
	Creator GLOSS Cetox 20 OE THIN 880	100 ml 2,5 ml max 8 ml	100 g 2 g max 5 g			
Add the thinner in the amount calculated for the mixture of Creator Gloss with CETOX 20 OE						
APPLICATION CONDITIONS						
It is recommended to apply the topcoat at a temperature above 10° C and a humidity of no more than 80 %.						



Creator Gloss

Technical Data Sheet 29.01.2025

29.01.2025							
APPLICATION	1			1			
	Conventional gravity fed spray gun	Nozzle	Pressure	Distance			
	CAUTION: Instructions of the equipment manufacturer must be followed	2.5 ÷ 3.0 mm	3 ÷ 4 bar	15 ÷ 20 cm			
	Number of layers	1 ÷ 2					
	Single wet layer thickness	Approx. 250 μm					
	The yield of the ready to use mixture for the given range of dry layer thickness	5.0 m²/l at 100 μm					
	Maximum total layer thickness	Approx. 500 μm					
X	Mixture life at 20 [°] C (for 100g mixture)		Approx. 100 minutes				
$\overline{\langle \uparrow \langle \uparrow \rangle}$	Flash off time between layers	Min. 5 ÷ 10 minutes					
DRYING TIMES							
\bigcirc	20°C	12 hours					
	60°C	60 min.					
CAUTION: The curing tim	nes apply to the temperatures of th	ne individual elements					
SANDING							
		MAX 2200 4		MAX 2200 4			
rough	finishing	Pre-polishing	Finis	hing polishing			
P360 ÷ P500	P600 ÷ P1500	Quattro – Polishi Compound	ng Quattro	– Finishing Glaze			
For more details see appropriate Technical Data Sheets Quattro products.							
COLOUR							
White							
EQUIPMENT CLEANING							
THIN 880 spray filler thin	ner or NC solvent						



29.01.2025

STORAGE CONDITIONS

Store in a cool, dry room, away from sources of fire and heat.

Avoid direct exposure to sunlight.

SHELF LIFE

Creator GLOSS	3 months/20°C
Cetox 20 OE	12 months/20°C
THIN 880	24 months/20°C

PACKAGING

Volume of packaging: 3,0 L Content of packaging: 2,7 L

SAFETY

See Safety Data Sheet

NOTES

Intended for professional use only. Use Creator Gloss only with the hardener Cetox 20OE and thinner THIN880.

Using other systems (hardener, thinner) may result in insufficient curing of the filler and flaws in coating.

OTHER INFORMATION

Registration number: 000024104

The effectiveness of our systems / products is the combined result of research conducted under controlled conditions in the NOVOL laboratory and our long experience. The data contained in this document reflects the current level of knowledge about our products, quality features (characteristics) and verified possibilities (conditions) of their use. We ensure the high quality of the product, provided that the user follows the instructions (guidelines included in the product data sheet) and the work is performed in accordance with good workmanship. Due to numerous factors that may affect the working conditions and the use of our systems / products, the recipient or user of the products is required to carry out their own tests and experiments, on the basis of which they can determine the fitness of a chosen product for a given application. The product is intended for use by professionals, at their own risk and responsibility.

In view of the above, NOVOL does not provide any legally binding guarantees as to specific characteristics or fitness for a particular purpose. The principles of liability of NOVOL are set out in the <u>General Terms and Conditions of Sale of Nautic Products (OWS NAUTIC) available</u> <u>at https://nautic.novol.com/uploads/OWS-nautic.pdf</u>.

It is the responsibility of the recipient or user of our systems / products to comply with property rights as well as the applicable laws and other regulations. The recipient or user should use the latest appropriate version of the product data sheet and the current version of the EU safety data sheet.