




Technical Data Sheet  
**PLUS 951**  
Accelerating agent for basecoats  
Hardener for basecoats

DESCRIPTION		
PLUS 951 is the product for hardening the Novobase 5020 basecoats which improves hardness and chemical resistance, and accelerates drying.		
MIXING RATIO		
	Volume ratio	Weight ratio
NOVOBASE 5020	100	100
PLUS 951	10%	10
COLOUR		
Colourless.		
EQUIPMENT CLEANING		
THIN 50 universal thinner.		
INFORMATION SIGNS		
		
Keep closed	Store in a cool room	Protect from frost
STORAGE TIME AND CONDITIONS		
Store in a dry room, away from sources of flame and heat. Avoid direct exposure to sunlight. Recommended storage temperature: +5°C to +35°C. Protect from frost.		
SHELF LIFE		
6 months at 20°C		
SAFETY REGULATIONS		
See the Safety Data Sheet.		
OTHER INFORMATION		
<p>Registration number: 000024104.</p> <p>The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.</p>		