

Technical data sheet
PLUS 770
Elasticity increasing agent

PROPERTIES	
PLUS 770 ELASTICITY INCREASING AGENT – is a plasticiser for acrylic and polyurethane products and primarily intended for use on plastic body parts. The product prevents cracking and chipping of the primer/filler and paint coating on elastic and deformable elements. It can also be used to elasticise paint coatings on metal elements exposed to stone chipping (e.g. front strip, bonnet).	
APPLICATION:	
The PLUS 770 elasticity increasing agent can be used for two-component acrylic products by Novol (primers, clearcoats and topcoats).	
MIXING RATIO	
To increase the paint coating's elasticity on plastic elements or to increase the coating's resistance to stone chipping (e.g. front strip, bonnet), add 10 – 30 % of PLUS 770 per the ready to apply mixture of the elasticised product with the hardener, correcting the amount of the thinner accordingly. Example: with 15% per 1 litre of mixture, add 0.15L of PLUS 770.	
COLOUR	
Colourless	
STORAGE CONDITIONS	
Store in a cool dry room, away from sources of fire and heat. Avoid direct exposure to sunlight.	
SHELF LIFE	
PLUS 770	24 months/20°C
SAFETY	
See Safety Data Sheet.	
OTHER INFORMATION	
The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.	