

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 6/15/2023 Revision date: 6/15/2023 Version: 1.00

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form: MixtureName: Bedliner - ETrade name: COBRA SFVaporizer: Aerosol	Black PRAY 2K DTM
---	----------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture

: The product is intended for professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o. Żabikowska 7/9 62-052 KOMORNIKI Poland T 0048618109800 - F 0048618109809 www.novol.com E-mail address of competent person responsible for the SDS : <u>dokumentacja@novol.com</u>

1.4. Emergency telephone number

Emergency number	: 112
------------------	-------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling ac	cording to	Regulation ((EC) No.	1272/2008	CLP1
East and a second second	Joonaning to	nogalation (<u> </u>

Hazard pictograms (CLP)

Signal word (CLP) Contains Hazard statements (CLP)



- : Danger
- : xylene; dimethyl ether
- : H222 Extremely flammable aerosol.
 - H229 Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

	H332 - Harmful if inhaled.
	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP) :	P102 - Keep out of reach of children.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
	P260 - Do not breathe vapours, spray.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves, protective clothing, eye protection, face protection.
	P312 - Call doctor if you feel unwell.
	P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122
	°F.
EUH-statements :	EUH204 - Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	< 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
dimethyl ether substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note U)	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128- 37	< 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
acetone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330- 49	< 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hexamethylen-1,6-Diisocyanat Homopolimer	CAS-No.: 28182-81-2 EC-No.: 500-060-2 REACH-no: 01-2119485796- 17	< 10	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
trizinc bis(orthophosphate)	CAS-No.: 7779-90-0 EC-No.: 231-944-3 EC Index-No.: 030-011-00-6 REACH-no: 01-2119485044- 40	< 2.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493- 29	< 1	Flam. Liq. 3, H226 STOT SE 3, H336

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:. Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

1 1 Description of first aid measures

4.1. Description of first aid measures	
First-aid measures general First-aid measures after inhalation	 General information. Refer to section 11. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	 After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.
4.2. Most important symptoms and effect	cts, both acute and delayed
Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact	 Vapours may cause drowsiness and dizziness. Prolonged or repeated contact may cause skin to become dry. May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Dry chemical, CO2, alcohol-resistant foam or waterspray.Do not use a heavy water stream.
5.2. Special hazards arising from the subs	tance or mixture
Hazardous decomposition products in case of fire	: Carbon monoxide. Other toxic gases.
5.3. Advice for firefighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures 6.1.1. For non-emergency personnel

5 71	
Protective equipment	: Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. See Section 8.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

6.3. Methods and material for containment and cleaning up

For containment

: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.

6.4. Reference to other sections

Disposal considerations. See Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Pressurized container. Do not spray on an open flame or other ignition source. Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including a	ny incompatibilities
Technical measures Storage conditions	 Ground/bond container and receiving equipment. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from ignition sources. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep out of reach of children.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

acetone (67-64-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m ³
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOE	EL)
Local name	n-Butyl acetate
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m ³
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOE	EL)
Local name	Xylene, mixed isomers, pure
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m ³ o-,m-,p- or mixed isomers
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

xylene (1330-20-7)			
United Kingdom - Biological limit values	United Kingdom - Biological limit values		
Local name	Xylene, o-, m-, p- or mixed isomers		
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
dimethyl ether (115-10-6)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Dimethylether		
IOEL TWA [ppm]	1000 ppm		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	Dimethyl ether		
WEL TWA (OEL TWA) [1]	766 mg/m ³		
WEL TWA (OEL TWA) [2]	400 ppm		
WEL STEL (OEL STEL)	958 mg/m ³		
WEL STEL (OEL STEL) [ppm]	500 ppm		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		

8.1.2. Recommended monitoring procedures

Monitoring methods

Moni	toring methods	EN 482. Workplace exposure - General requirements for the performance of procedures
		for the measurement of chemical agents.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Black.
Appearance	: Aerosol.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: ≈ -25 °C
Flammability	: Not applicable
Explosive properties	: No data available.
Explosive limits	: Not available
Lower explosion limit	: 1.1 vol %
Upper explosion limit	: 18.6 vol %
Flash point	: ≈ -42 °C
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
рН	: Not available
Viscosity, kinematic	: Not available
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 3500 hPa
Vapour pressure at 50°C	: Not available
Density	: 0.8 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients

: < 90 %

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Prevent build-up of electrostatic charges (e.g, by grounding).

10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

	• • • •	
Acute toxicity (oral):Acute toxicity (dermal):Acute toxicity (inhalation):	Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Harmful if inhaled.	
COBRA SPRAY 2K DTM		
ATE CLP (dust,mist)	4.286 mg/l/4h	
acetone (67-64-1)	·	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female	
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA	
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4	
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA	
n-butyl acetate (123-86-4)		
LD50 oral rat	12.2 ml/kg Source: ECHA	
LC50 Inhalation - Rat (Vapours)	> 4.9 mg/l Source: ECHA	
trizinc bis(orthophosphate) (7779-90-0)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

trizinc bis(orthophosphate) (7779-90-0)	
LC50 Inhalation - Rat	> 5700 mg/m³ Source: ECHA
xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg rat
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	27124 mg/l
dimethyl ether (115-10-6)	
LC50 Inhalation - Rat	308.5 mg/l Source: International Uniform ChemicaL Information Database
LC50 Inhalation - Rat [ppm]	164000 ppm Animal: rat, Animal sex: male, 95% CL: 142000 - 203000
Hexamethylen-1,6-Diisocyanat Homopolir	mer (28182-81-2)
LD50 oral rat	> 2500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:
Skin corrosion/irritation	: Causes skin irritation.
n-butyl acetate (123-86-4)	
pН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity Reproductive toxicity	 May cause an allergic skin reaction. Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met)
acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
Hexamethylen-1,6-Diisocyanat Homopolir	ner (28182-81-2)
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

trizinc bis(orthophosphate) (7779-90-0)		
LOAEL (oral, rat, 90 days)	53.8 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity Study in Rodents)	
NOAEL (oral, rat, 90 days)	31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity Study in Rodents)	
xylene (1330-20-7)		
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)	
Aspiration hazard : I	Not classified (Based on available data, the classification criteria are not met)	
COBRA SPRAY 2K DTM		
Vaporizer	Aerosol	
n-butyl acetate (123-86-4)		
Viscosity, kinematic	0.83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : (acute) Hazardous to the aquatic environment, long-term : (chronic)	Not classified (Based on available data, the classification criteria are not met) Harmful to aquatic life with long lasting effects.
Not rapidly degradable	
acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l Source: ECHA
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	\geq 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Source: ECHA
EC50 - Crustacea [1] 44 mg/l Source: ECHA	
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

xylene (1330-20-7)		
NOEC chronic fish > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salr gairdneri) Duration: '56 d'		
dimethyl ether (115-10-6)		
LC50 - Fish [1]	> 4.1 g/l Test organisms (species): Poecilia reticulata	
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna	
EC50 96h - Algae [1]	154.917 mg/l Test organisms (species): other:green algae	
Hexamethylen-1,6-Diisocyanat Homopolimer (28182-81-2)		
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): other:	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

acetone (67-64-1)		
Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC	
n-butyl acetate (123-86-4)		
Partition coefficient n-octanol/water (Log Pow)	1.78 Source: HSDB	
dimethyl ether (115-10-6)		
Partition coefficient n-octanol/water (Log Pow)	0.1 Source: International Chemical Safety Cards	

12.4. Mobility in soil

dimethyl ether (115-10-6)	
Mobility in soil	27 Source: National Library of Medicine/Hazardous Substances Data Bank

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains.
Product/Packaging disposal recommendations	: This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
Additional information	: Flammable vapours may accumulate in the container.
European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
	15 01 10* - packaging containing residues of or contaminated by dangerous substances

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 14: Transport information

ADR	IMDG	ΙΑΤΑ	
14.1. UN number or ID number	· · · ·		
UN 1950	UN 1950	UN 1950	
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	Aerosols, flammable	
Transport document description			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1 (-42°C c.c.)	UN 1950 Aerosols, flammable, 2.1	
14.3. Transport hazard class(es)	-		
2.1	2.1	2.1	
14.4. Packing group	· · · ·		
Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	
No supplementary information available	1		

14.6. Special precautions for user

: 5F
: 11
: PP87, RR6, L2
: MP9
: 2
: V14
: D
: 63, 190, 277, 327, 344, 381, 959
: SP277
: PP87, L2
: F-D
: S-U
: None
: SW1, SW22
: SG69

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors) ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name		Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:			
ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways			
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE Acute Toxicity Estimate			

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:			
BCF	Bioconcentration factor		
BLV	Biological limit value		
BOD	Biochemical oxygen demand (BOD)		
COD	Chemical oxygen demand (COD)		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
VOC	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		
ED	Endocrine disrupting properties		

Data sources

: ECHA (European Chemicals Agency).

Training advice

: Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	on) Acute toxicity (inhal.), Category 4	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Acute Tox. 4 (Inhalation.dust,mist)Acte toxicity (inhalation.dust,mist)Category 4AerosolAerosol, Category 1Aquatic Acute 1Hazardous to the aquatic environment – Acute Hazard, Category 1Aquatic Chronic 1Hazardous to the aquatic environment – Chronic Hazard, Category 1Aquatic Chronic 3Hazardous to the aquatic environment – Chronic Hazard, Category 3EUH204Contains isocyanates. May produce an allergic reaction.Eyr Int. 2Serious eye damage/eye iritation. Category 2Flam. Gas 1AFlammable gases. Category 1AFlam. Liq. 2Flammable gases. Category 3Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gase.H221Katremely flammable acrosol.H222Extremely flammable acrosol.H223Flammable liquid and vapour.H224Pressurised container: May burst if heated.H235Qontains gas under pressure; may explode if heated.H316Causes skin irritation.H317May cause an allergic skin reaction.H318Cause skin irritation.H324Harmful in contact with skin.H335May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life.H410Very toxic to aquatic life.H412Harmful to consels or dizziness.H411Serious eye analergic skin gefects.Press. Gas (Comp.).Gases under pressure: Compressed gasSkin Int. 2Skin sensilisation, Category 2Skin Int. 2Sk	Full text of H- and El	JH-statements:		
Aquatic Acute 1Hazardous to the aquatic environment – Acute Hazard, Category 1Aquatic Chronic 1Hazardous to the aquatic environment – Chronic Hazard, Category 1Aquatic Chronic 3Hazardous to the aquatic environment – Chronic Hazard, Category 3EUH204Contains isocyanates. May produce an allergic reaction.Eye Irrit. 2Serious eye damage/eye irritation, Category 2Flam. Gas 1AFlammable gases, Category 1AFlam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable ilquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable gas.H225Highly flammable ilquid and vapour.H226Pressurised container: May burst if heated.H237Harmful in contact with skin.H318Causes skin irritation.H319Causes skin irritation.H319Causes skin irritation.H320Way cause an allergic skin reaction.H332Harmful i finhaled.H335May cause ording irritation.H336May cause ording irritation.H336Very toxic to aquatic ife.H400Very toxic to aquatic fife.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin orrosion/irritation, Category 2Skin sensi.1Skin Sens. 1Skin sensiliation, Category 1		Acute toxicity (inhalation:dust,mist) Category 4		
Aquatic Chronic 1Hazardous to the aquatic environment – Chronic Hazard, Category 1Aquatic Chronic 3Hazardous to the aquatic environment – Chronic Hazard, Category 3EUH204Contains isocyanates. May produce an allergic reaction.Eye Irit. 2Serious eye damage/eye irritation, Category 2Flam. Gas 1AFlammable gases, Category 1AFlam. Liq. 2Flammable liquids, Category 3Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable gas.H223Highly flammable aerosol.H224Flammable liquid and vapour.H225Highly flammable gas.H226Flammable liquid and vapour.H227Extremely flamin, burst if heated.H230Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H316Causes skin irritation.H332Harmful if inhaled.H334May cause or allergic skin reaction.H335May cause or disziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life.H412Harmful to aquatic life with long lasting effects.H412Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitiation, Category 2	Aerosol 1	Aerosol, Category 1		
Aquatic Chronic 3Hazardous to the aquatic environment - Chronic Hazard, Category 3EUH204Contains isocyanates. May produce an allergic reaction.Eye Irit. 2Serious eye damage/eye irritation, Category 2Flam. Gas 1AFlammable gases, Category 1AFlam. Liq, 2Flammable liquids, Category 2Flam. Liq, 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable aerosol.H223Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H316Causes scious eye irritation.H317May cause an allergic skin reaction.H318May cause respiratory irritation.H332Harmful if inhaled.H335May cause drowsiness or dizzness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H712Harmful to aquatic life with long lasting effects.H713Skin corrosion/irritation, Category 2Skin Irrit. 2Skin sensiti, Category 2	Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
EUH204Contains isocyanates. May produce an allergic reaction.Eye Irrit. 2Serious eye damage/eye irritation, Category 2Flam. Gas 1AFlammable gases, Category 1AFlam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable liquid and vapour.H223Highly flammable liquid and vapour.H224Flammable liquid and vapour.H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.H227Ontains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H332Harmful if inhaled.H333May cause respiratory irritation.H334May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Sens. 1Skin sensitisation, Category 2Skin Sens. 1Skin sensitisation, Category 2	Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Eye Irrit. 2Serious eye damage/eye irritation, Category 2Flam. Gas 1AFlammable gases, Category 1AFlam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable aerosol.H223Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H220Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H332Harmful if inhaled.H333May cause respiratory irritation.H336May cause or diztiness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.H412Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensifisation, Category 1	Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Flam. Gas 1AFlammable gases, Category 1AFlam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable aerosol.H223Highly flammable liquid and vapour.H226Flamsable ilquid and vapour.H229Pressurised container: May burst if heated.H280Containes gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H319Causes serious eye irritation.H336May cause an allergic skin reaction.H336May cause or diziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life.H412Harmful to aquatic life with long lasting effects.H412Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensilisation, Category 2	EUH204	Contains isocyanates. May produce an allergic reaction.		
Flam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable acrosol.H222Extremely flammable liquid and vapour.H226Flammable liquid and vapour.H227Flammable liquid and vapour.H228Flammable liquid and vapour.H229Pressurised container: May burst if heated.H230Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H338Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.H412Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitisation, Category 1	Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable aerosol.H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause freises or dizziness.H400Very toxic to aquatic life.H411Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.H412Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitisation, Category 1	Flam. Gas 1A	Flammable gases, Category 1A		
H220Extremely flammable gas.H222Extremely flammable aerosol.H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H220Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H319Causes serious eye irritation.H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H411Harmful to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin sensitisation, Category 1	Flam. Liq. 2	Flammable liquids, Category 2		
H222Extremely flammable aerosol.H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H338Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Fress. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 1	Flam. Liq. 3	Flammable liquids, Category 3		
H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H319Causes serious eye irritation.H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 1	H220	Extremely flammable gas.		
H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H316Causes skin irritation.H317May cause an allergic skin reaction.H319Causes serious eye irritation.H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 1	H222	Extremely flammable aerosol.		
H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H315Causes skin irritation.H317May cause an allergic skin reaction.H319Causes serious eye irritation.H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin sensitisation, Category 1	H225	Highly flammable liquid and vapour.		
H280Contains gas under pressure; may explode if heated.H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H319Causes serious eye irritation.H322Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 1	H226	Flammable liquid and vapour.		
H312Harmful in contact with skin.H315Causes skin irritation.H317May cause an allergic skin reaction.H319Causes serious eye irritation.H322Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 1	H229	Pressurised container: May burst if heated.		
H315Causes skin irritation.H317May cause an allergic skin reaction.H319Causes serious eye irritation.H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 1	H280	Contains gas under pressure; may explode if heated.		
H317May cause an allergic skin reaction.H319Causes serious eye irritation.H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 2Skin Sens. 1Kin sensitisation, Category 1	H312	Harmful in contact with skin.		
H319Causes serious eye irritation.H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin sensitisation, Category 1	H315	Causes skin irritation.		
H332Harmful if inhaled.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.		
H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitisation, Category 1	H319	Causes serious eye irritation.		
H336May cause drowsiness or dizziness.H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitisation, Category 1	H332	Harmful if inhaled.		
H400Very toxic to aquatic life.H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitisation, Category 1	H335	May cause respiratory irritation.		
H410Very toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitisation, Category 1	H336	May cause drowsiness or dizziness.		
H412Harmful to aquatic life with long lasting effects.Press. Gas (Comp.)Gases under pressure : Compressed gasSkin Irrit. 2Skin corrosion/irritation, Category 2Skin Sens. 1Skin sensitisation, Category 1	H400	Very toxic to aquatic life.		
Press. Gas (Comp.) Gases under pressure : Compressed gas Skin Irrit. 2 Skin corrosion/irritation, Category 2 Skin Sens. 1 Skin sensitisation, Category 1	H410	Very toxic to aquatic life with long lasting effects.		
Skin Irrit. 2 Skin corrosion/irritation, Category 2 Skin Sens. 1 Skin sensitisation, Category 1	H412	Harmful to aquatic life with long lasting effects.		
Skin Sens. 1 Skin sensitisation, Category 1	Press. Gas (Comp.)	Gases under pressure : Compressed gas		
	Skin Irrit. 2	Skin corrosion/irritation, Category 2		
STOT SE 3 Specific target organ toxicity – Single exposure, Category 3, Narcosis	Skin Sens. 1	Skin sensitisation, Category 1		
	STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Aerosol 1	H222;H229	On basis of test data	
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method	
Skin Irrit. 2	H315	Calculation method	
Skin Sens. 1	H317	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

Safety Data Sheet (SDS), EU

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.