

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Name : Acrylic Clearcoat  
Trade name : KLAR 525-00

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Use of the substance/mixture : The product is intended for professional use

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****Supplier**

NOVOL Sp. z o.o.  
Żabikowska 7/9  
62-052 KOMORNIKI  
Poland  
T 0048618109800 - F 0048618109809

[www.novol.com](http://www.novol.com)

E-mail address of competent person responsible for the SDS :

[dokumentacja@novol.com](mailto:dokumentacja@novol.com)

**1.4. Emergency telephone number**

Emergency number : 112

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger  
Contains : isobutyl methyl ketone  
Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Precautionary statements (CLP)	H336 - May cause drowsiness or dizziness. H351 - Suspected of causing cancer. H412 - Harmful to aquatic life with long lasting effects. : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P312 - Call doctor if you feel unwell.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336
heptan-2-one; methyl amyl ketone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 110-43-0 EC-No.: 203-767-1 EC Index-No.: 606-024-00-3 REACH-no: 01-2119902391-49	10 – 15	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
isobutyl methyl ketone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-10-1 EC-No.: 203-550-1 EC Index-No.: 606-004-00-4 REACH-no: 01-2119473980-30	5 – 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336
Hydrocarbons, C9, aromatics	EC-No.: 918-668-5 REACH-no: 01-2119455851-35	< 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS-No.: 104810-48-2+104810-47-1+ 25322-68-3 EC-No.: 400-830-7 EC Index-No.: 607-176-00-3 REACH-no: 01-2119472279-28	$\leq 1$	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	CAS-No.: 41556-26-7 EC-No.: 255-437-1	< 0.4	Skin Sens. 1, H317 Aquatic Chronic 1, H410 (M=10)

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
pentaerythritol tetrakis(3-mercaptopropionate)	CAS-No.: 7575-23-7 EC-No.: 231-472-8 REACH-no: 01-2119486981-23	< 0.1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: General information. Refer to section 11.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	: Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: May cause eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical, CO <sub>2</sub> , alcohol-resistant foam or waterspray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Carbon monoxide. Other toxic gases.
--	---------------------------------------

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.
----------------------	--

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

### 6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.

### 6.4. Reference to other sections

Disposal considerations. See Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m <sup>3</sup>
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	200 ppm

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>n-butyl acetate (123-86-4)</b>	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>heptan-2-one; methyl amyl ketone (110-43-0)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Heptan-2-one
IOEL TWA [ppm]	50 ppm
IOEL STEL	475 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Heptan-2-one
WEL TWA (OEL TWA) [1]	237 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	475 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>isobutyl methyl ketone (108-10-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	4-Methylpentan-2-one
IOEL TWA [ppm]	20 ppm
IOEL STEL	208 mg/m <sup>3</sup>
IOEL STEL [ppm]	50 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	4-Methylpentan-2-one
WEL TWA (OEL TWA) [1]	208 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	4-methylpentan-2-one
BMGV	20 µmol/l Parameter: 4-methylpentan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

n-butyl acetate (123-86-4)	
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.0903 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	35.6 mg/l
<b>Hydrocarbons, C9, aromatics</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	150 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	11 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	32 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11 mg/kg bodyweight/day
<b>heptan-2-one; methyl amyl ketone (110-43-0)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	1516 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	54.27 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	394.25 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	23.32 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	84.31 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	23.32 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.0982 mg/l
PNEC aqua (marine water)	0.00982 mg/l
PNEC aqua (intermittent, freshwater)	0.982 mg/l

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>heptan-2-one; methyl amyl ketone (110-43-0)</b>	
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	1.89 mg/kg dwt
PNEC sediment (marine water)	0.189 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.321 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	12.5 mg/l
<b>pentaerythritol tetrakis(3-mercaptopropionate) (7575-23-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	40.13 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.74 mg/m <sup>3</sup>
Long-term - local effects, inhalation	40.13 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - local effects, inhalation	20.07 mg/m <sup>3</sup>
Long-term - systemic effects, oral	0.25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.43 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	2.5 mg/kg bodyweight/day
Long-term - local effects, inhalation	20.07 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.03 µg/l
PNEC aqua (marine water)	3.4 ng/l
PNEC aqua (intermittent, freshwater)	0.34 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	1.02 µg/kg dw
PNEC sediment (marine water)	0.102 µg/kg dw
<b>PNEC (Soil)</b>	
PNEC soil	0.184 µg/kg dw
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	2.39 mg/l
<b>isobutyl methyl ketone (108-10-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	208 mg/m <sup>3</sup>
Acute - local effects, inhalation	208 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11.8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	83 mg/m <sup>3</sup>
Long-term - local effects, inhalation	83 mg/m <sup>3</sup>

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>isobutyl methyl ketone (108-10-1)</b>	
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	155.2 mg/m <sup>3</sup>
Acute - local effects, inhalation	155.2 mg/m <sup>3</sup>
Long-term - systemic effects, oral	4.2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.7 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	4.2 mg/kg bodyweight/day
Long-term - local effects, inhalation	14.7 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.6 mg/l
PNEC aqua (marine water)	0.06 mg/l
PNEC aqua (intermittent, freshwater)	1.5 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	8.27 mg/kg dwt
PNEC sediment (marine water)	0.83 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	1.3 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	27.5 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves



# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 114 – 117 °C
Flammability	: Not applicable
Explosive properties	: No data available.
Explosive limits	: Not available
Lower explosion limit	: 1.3 vol % 4-methylpentan-2-one; isobutyl methyl ketone
Upper explosion limit	: 8 vol % 4-methylpentan-2-one; isobutyl methyl ketone
Flash point	: 14 °C
Auto-ignition temperature	: ≈ 370 °C
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: Not available
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 21 hPa
Vapour pressure at 50°C	: Not available
Density	: 1 g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g. by grounding). Protect from sunlight. Avoid high temperatures.

#### 10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	12.2 ml/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 4.9 mg/l Source: ECHA
<b>Hydrocarbons, C9, aromatics</b>	
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 6193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
<b>heptan-2-one; methyl amyl ketone (110-43-0)</b>	
LD50 oral rat	≈ 1600 mg/kg bodyweight Animal: rat, Remarks on results: other:
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 16.7 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))
LC50 Inhalation - Rat (Vapours)	> 16.7 mg/l Source: ECHA
<b>pentaerythritol tetrakis(3-mercaptopropionate) (7575-23-7)</b>	
LD50 oral rat	1000 – 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Remarks on results: other:
LC50 Inhalation - Rat	> 3363 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity), Remarks on results: other:

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>isobutyl methyl ketone (108-10-1)</b>	
LD50 oral rat	2080 mg/kg Source: ECHA
LD50 dermal rabbit	≥ 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.6 mg/l Source: ECHA
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
LD50 oral rat	2369 – 3920 mg/kg Source: International Uniform Chemical Information Database
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
<b>n-butyl acetate (123-86-4)</b>	
pH	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
<b>n-butyl acetate (123-86-4)</b>	
pH	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Suspected of causing cancer.
<b>isobutyl methyl ketone (108-10-1)</b>	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Hydrocarbons, C9, aromatics</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
<b>isobutyl methyl ketone (108-10-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
<b>n-butyl acetate (123-86-4)</b>	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
<b>Hydrocarbons, C9, aromatics</b>	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
<b>pentaerythritol tetrakis(3-mercaptopropionate) (7575-23-7)</b>	
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
<b>isobutyl methyl ketone (108-10-1)</b>	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>isobutyl methyl ketone (108-10-1)</b>	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

<b>n-butyl acetate (123-86-4)</b>	
Viscosity, kinematic	0.83 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
<b>heptan-2-one; methyl amyl ketone (110-43-0)</b>	
Viscosity, kinematic	0.979 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Not rapidly degradable

<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l Source: ECHA
EC50 - Crustacea [1]	44 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

<b>Hydrocarbons, C9, aromatics</b>	
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

<b>heptan-2-one; methyl amyl ketone (110-43-0)</b>	
LC50 - Fish [1]	131 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 90.1 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	98.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	75.5 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>pentaerythritol tetrakis(3-mercaptopropionate) (7575-23-7)</b>	
LC50 - Fish [1]	0.034 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 0.35 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 0.12 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	2.909 mg/l Source: Ecological Structure Activity Relationships
<b>isobutyl methyl ketone (108-10-1)</b>	
LC50 - Fish [1]	> 179 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
LC50 - Fish [1]	0.97 mg/l Source: International Uniform Chemical Information Database
EC50 96h - Algae [1]	0.017 mg/l Source: Ecological Structure Activity Relationships

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>n-butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.78 Source: HSDB
<b>heptan-2-one; methyl amyl ketone (110-43-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.26 Source: ECHA
<b>isobutyl methyl ketone (108-10-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.31 Source: ChemIDPlus
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.37 Source: International Uniform Chemical Information Database

### 12.4. Mobility in soil

<b>pentaerythritol tetrakis(3-mercaptopropionate) (7575-23-7)</b>	
Mobility in soil	225300 Source: Quantitative Structure Activity Relation

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

# KLAR 525-00




## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Sewage disposal recommendations	: Do not discharge into drains.
Product/Packaging disposal recommendations	: This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
Additional information	: Flammable vapours may accumulate in the container.
European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
<b>14.1. UN number or ID number</b>		
UN 1866	UN 1866	UN 1866
<b>14.2. UN proper shipping name</b>		
RESIN SOLUTION	RESIN SOLUTION	Resin solution
<b>Transport document description</b>		
UN 1866 RESIN SOLUTION, 3, II, (D/E)	UN 1866 RESIN SOLUTION, 3, II (14°C c.c.)	UN 1866 Resin solution, 3, II
<b>14.3. Transport hazard class(es)</b>		
3	3	3
		
<b>14.4. Packing group</b>		
II	II	II
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Transport category (ADR)	: 2

Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

#### Transport by sea

Limited quantities (IMDG)	: 5 L
Special packing provisions (IMDG)	: PP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

#### Air transport

No data available

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Abbreviations and acronyms:</b>	
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : ECHA (European Chemicals Agency).

Training advice : Handle in accordance with good industrial hygiene and safety procedures.

<b>Full text of H- and EUH-statements:</b>	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.



# KLAR 525-00

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	On basis of test data
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Expert judgment

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.