

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 8/11/2023 Revision date: 10/11/2023 Supersedes version of: 8/11/2023 Version: 2.00

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Name : Direct acrylic-polyurethane topcoat - matt

Trade name : NOVORUST 2020 DTM NF

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : The product is intended for professional use

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o. Żabikowska 7/9

62-052 KOMORNIKI - Poland

Poland

T 0048618109800 - F 0048618109809 sekretariat@novol.com - www.novol.com

E-mail address of competent person responsible for the SDS : dokumentacja@novol.com

#### 1.4. Emergency telephone number

Emergency number : 112

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

No additional information available

# 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02

GHS07

Signal word (CLP) : Warning
Contains : xylene

Hazard statements (CLP) : H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing vapours, spray.

P271 - Use only outdoors or in a well-ventilated area.

10/11/2023 (Revision date) GB - en 1/16

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

P280 - Wear protective gloves, protective clothing, eye protection, face protection. P312 - Call doctor if you feel unwell.

## 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	< 38	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315
n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493- 29	< 12	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
Hydrocarbons, C9, aromatics	EC-No.: 918-668-5 REACH-no: 01-2119455851- 35	< 8	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 (M=1) EUH066
reaction mass of N, N'-ethane1,2-diylbis(hexanamide) and 12-hydroxy-N-[2-[(1-oxyhexyl)amino]ethyl]octadecanamide and N, N'-ethane-1,2-diylbis(12-hydroxyoctadecan amide)	EC-No.: 432-430-3 EC Index-No.: 616-200-00-1 REACH-no: 01-0000017860-	< 1.6	Aquatic Chronic 4, H413
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-	<1	Flam. Liq. 3, H226
2-Methoxypropyl acetate; 2-Methoxy-1-propyl acetate	CAS-No.: 70657-70-4 EC-No.: 274-724-2 EC Index-No.: 607-251-00-0	< 0.00125	Flam. Liq. 3, H226 Repr. 1B, H360D STOT SE 3, H335

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H- and EUH-statements: see section 16

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : General information. Refer to section 11.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash

immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse

immediately with plenty of water and seek medical advice.

First-aid measures after ingestion : If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Vapours may cause drowsiness and dizziness.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : May cause eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO2, alcohol-resistant foam or waterspray.

Unsuitable extinguishing media : Do not use a heavy water stream.

## 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon monoxide. Other toxic gases.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

Protective equipment : Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct

or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.

protective equipment as required. See Section of

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

#### 6.2. Environmental precautions

6.1.2. For emergency responders

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

#### 6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically

recover the product.

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 6.4. Reference to other sections

Disposal considerations. See Section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking. Use only outdoors or in a well-

ventilated area. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be

allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Storage temperature : 5-35 °C

## 7.3. Specific end use(s)

No additional information available

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

xylene (1330-20-7)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	Xylene, mixed isomers, pure		
IOEL TWA [ppm]	50 ppm		
IOEL STEL	442 mg/m³		
IOEL STEL [ppm]	100 ppm		
Remark	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limits			
Local name	Xylene		
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers		
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers		
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers		
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers		
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
United Kingdom - Biological limit values			
Local name	Xylene, o-, m-, p- or mixed isomers		
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

xylene (1330-20-7)				
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
	ZTTTO/ZOOG (F Gattin Gatton), ZGZS/, TTGZ			
	n-butyl acetate (123-86-4)			
EU - Indicative Occupational Exposure Limit (IOEL)				
Local name	n-Butyl acetate			
IOEL TWA [ppm]	50 ppm			
IOEL STEL	723 mg/m³			
IOEL STEL [ppm]	150 ppm			
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831			
United Kingdom - Occupational Exposure Limits				
Local name	Butyl acetate			
WEL TWA (OEL TWA) [1]	724 mg/m³			
WEL TWA (OEL TWA) [2]	150 ppm			
WEL STEL (OEL STEL)	966 mg/m³			
WEL STEL (OEL STEL) [ppm]	200 ppm			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
2-methoxy-1-methylethyl acetate (108-65-6)				
EU - Indicative Occupational Exposure Limit (IOEL)				
Local name	2-Methoxy-1-methylethylacetate			
IOEL TWA [ppm]	50 ppm			
IOEL STEL	550 mg/m³			
IOEL STEL [ppm]	100 ppm			
Remark	Skin			
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC			
United Kingdom - Occupational Exposure Limits				
Local name	1-Methoxypropyl acetate			
WEL TWA (OEL TWA) [1]	274 mg/m³			
WEL TWA (OEL TWA) [2]	50 ppm			
WEL STEL (OEL STEL)	548 mg/m³			
WEL STEL (OEL STEL) [ppm]	100 ppm			
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			

# 8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	EN 482. Workplace exposure - General requirements for the performance of procedures
	for the measurement of chemical agents.

# 8.1.3. Air contaminants formed

No additional information available

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 8.1.4. DNEL and PNEC

L (4000 00 T)		
xylene (1330-20-7)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	289 mg/m³	
Acute - local effects, inhalation	289 mg/m³	
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	77 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	174 mg/m³	
Acute - local effects, inhalation	174 mg/m³	
Long-term - systemic effects,oral	1.6 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	14.8 mg/m³	
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.327 mg/l	
PNEC aqua (marine water)	0.327 mg/l	
PNEC aqua (intermittent, freshwater)	0.327 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	12.46 mg/kg dwt	
PNEC sediment (marine water)	12.46 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2.31 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	6.58 mg/l	
n-butyl acetate (123-86-4)		
PNEC (Water)		
PNEC aqua (freshwater)	0.18 mg/l	
PNEC aqua (marine water)	0.018 mg/l	
PNEC aqua (intermittent, freshwater)	0.36 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.981 mg/kg dwt	
PNEC sediment (marine water)	0.0981 mg/kg dwt	
PNEC (Soil)	1	
PNEC soil	0.0903 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	35.6 mg/l	
2-methoxy-1-methylethyl acetate (108-65-6)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	550 mg/m³	
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day	
<u> </u>		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2-methoxy-1-methylethyl acetate (108-65-6)		
Long-term - systemic effects, inhalation	275 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	36 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	33 mg/m³	
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day	
Long-term - local effects, inhalation	33 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.635 mg/l	
PNEC aqua (marine water)	0.0635 mg/l	
PNEC aqua (intermittent, freshwater)	6.35 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3.29 mg/kg dwt	
PNEC sediment (marine water)	0.329 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.29 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	

## 8.1.5. Control banding

No additional information available

# 8.2. Exposure controls

# 8.2.1. Appropriate engineering controls

## Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

## Personal protective equipment symbol(s):







# 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses

# 8.2.2.2. Skin protection

## Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Colourless. Odour : characteristic. Odour threshold : 0.9 – 9 mg/m³ Xylene Melting point : Not applicable Freezing point : Not available : 120 - 140 °C Boiling point Flammability : Not applicable Explosive properties : No data available. Explosive limits : Not available Lower explosion limit : 1.1 vol % Xylene Upper explosion limit : 8 vol % Xylene : 24 °C Flash point Auto-ignition temperature : 415 °C Decomposition temperature : Not available : Not available Viscosity, kinematic : Not available

Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : 9 hPa Vapour pressure at  $50^{\circ}$ C : Not available Density : ≈ 1.3 g/cm³ Relative density : Not available Relative vapour density at  $20^{\circ}$ C : Not available Particle characteristics : Not applicable

#### 9.2. Other information

Solubility

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

## 9.2.2. Other safety characteristics

No additional information available

: Slightly soluble.

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g, by grounding). Protect from sunlight. Avoid high temperatures.

#### 10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

## 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon monoxide. Other toxic gases.

### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)

: Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal)

: Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation)

: Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (innalation)	: Not classified. (Based on available data, the classification criteria are not met)
xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg rat
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	27124 mg/l
n-butyl acetate (123-86-4)	
LD50 oral rat	12.2 ml/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 4.9 mg/l Source: ECHA
2-methoxy-1-methylethyl acetate (108-	65-6)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C9, aromatics	
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 6193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
reaction mass of N, N'-ethane1,2-diylb and N, N'-ethane-1,2-diylbis(12-hydrox	is(hexanamide) and 12-hydroxy-N-[2-[(1-oxyhexyl)amino]ethyl]octadecanamide yoctadecan amide)
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method), Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

and N, N'-ethane-1,2-diylbis(12-hydr	oxyoctadecan amide)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
Skin corrosion/irritation	: Causes skin irritation.
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C9, aromatics	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
2-Methoxypropyl acetate; 2-Methox	y-1-propyl acetate (70657-70-4)
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity Rodents)
2-methoxy-1-methylethyl acetate (10	08-65-6)
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Hydrocarbons, C9, aromatics	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
reaction mass of N, N'-ethane1,2-diy and N, N'-ethane-1,2-diylbis(12-hydr	/lbis(hexanamide) and 12-hydroxy-N-[2-[(1-oxyhexyl)amino]ethyl]octadecanamide
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90 Day Oral Toxicity Study in Rodents)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

n-butyl acetate (123-86-4)	
Viscosity, kinematic	0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

## 11.2. Information on other hazards

No additional information available

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

Not rapidly degradable

: Not classified (Based on available data, the classification criteria are not met)

: Harmful to aquatic life with long lasting effects.

xylene (1330-20-7)		
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia	
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'	
n-butyl acetate (123-86-4)		
LC50 - Fish [1]	18 mg/l Source: ECHA	
EC50 - Crustacea [1]	44 mg/l Source: ECHA	
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina	
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
2-methoxy-1-methylethyl acetate (108-6	<del>35-6)</del>	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes	
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'	
Hydrocarbons, C9, aromatics	·	
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
2-Methoxypropyl acetate ; 2-Methoxy-1	-propyl acetate (70657-70-4)	
LC50 - Fish [1]	123.852 mg/l Source: Ecological Structure Activity Relationships	

10/11/2023 (Revision date) GB - en 11/16

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2-Methoxypropyl acetate ; 2-Methoxy-1-propyl acetate (70657-70-4)		
EC50 96h - Algae [1] 9.337 mg/l Source: Ecological Structure Activity Relationships		
reaction mass of N, N'-ethane1,2-diylbis(hexanamide) and 12-hydroxy-N-[2-[(1-oxyhexyl)amino]ethyl]octadecanamide and N, N'-ethane-1,2-diylbis(12-hydroxyoctadecan amide)		
LOEC (chronic) 2.5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	0.9 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	

## 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1.78 Source: HSDB

## 12.4. Mobility in soil

2-Methoxypropyl acetate ; 2-Methoxy-1-propyl acetate (70657-70-4)	
Mobility in soil	1.838 Source: Quantitative Structure Activity Relation

#### 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Regional legislation (waste)

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

European List of Waste (LoW) code

: Disposal must be done according to official regulations.

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

: Do not discharge into drains.

: This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.

: Flammable vapours may accumulate in the container.

: 08 01 11\* - waste paint and varnish containing organic solvents or other dangerous

substances

15 01 10\* - packaging containing residues of or contaminated by dangerous substances

#### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA	
14.1. UN number or ID number			
UN 1866	UN 1866	UN 1866	
14.2. UN proper shipping name			
RESIN SOLUTION	RESIN SOLUTION	Resin solution	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

IMDG	IATA
UN 1866 RESIN SOLUTION, 3, III (24°C c.c.)	UN 1866 Resin solution, 3, III
3	3
3	3
III	III
Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
	UN 1866 RESIN SOLUTION, 3, III (24°C c.c.)  3  III  Dangerous for the environment: No

## 14.6. Special precautions for user

#### **Overland transport**

: F1 Classification code (ADR) Limited quantities (ADR) : 51 Special packing provisions (ADR) : PP1 Mixed packing provisions (ADR) : MP19 Transport category (ADR) : 3 Special provisions for carriage - Packages (ADR) : V12 Tunnel restriction code (ADR) : D/E EAC code : •3Y

# Transport by sea

Special provisions (IMDG) : 223, 955
Limited quantities (IMDG) : 5 L
Special packing provisions (IMDG) : PP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

#### Air transport

No data available

# 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.1.1. EU-Regulations

## **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

## **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

# **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

#### **SECTION 16: Other information**

#### Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:			
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
BLV	Biological limit value		
BOD	Biochemical oxygen demand (BOD)		
COD	Chemical oxygen demand (COD)		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:		
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Data sources : ECHA (European Chemicals Agency).

Training advice : Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH066	Repeated exposure may cause skin dryness or cracking.	
Flam. Liq. 3	Flammable liquids, Category 3	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H360D	May damage the unborn child.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:		
Repr. 1B	Reproductive toxicity, Category 1B	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	Expert judgement
Skin Irrit. 2	H315	Expert judgement
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.