

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Name : Epoxy putty hardener
Trade name : MARINEPRO EPOXY PUTTY HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Professional use
Use of the substance/mixture : Hardener
The product is intended for professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Manufacturer**

NOVOL Sp. z o.o.
Żabikowska 7/9
62-052 KOMORNIKI, Poland
Poland
T +48618109800, F +48618109809
sekretariat@novol.com, www.novol.com
E-mail address of competent person responsible for the SDS :
dokumentacja@novol.com

1.4. Emergency telephone number

Emergency number : 112

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Skin corrosion/irritation, Category 1, Sub-Category 1B H314
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, category 1A H317
Reproductive toxicity, Category 2 H361d
Hazardous to the aquatic environment – Chronic Hazard, H412
Category 3
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)



Signal word (CLP) : Danger
Contains : salicylic acid; m-phenylenebis(methylamine)

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hazard statements (CLP)	: H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H361d - Suspected of damaging the unborn child. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P260 - Do not breathe vapours. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl alcohol	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-38	15 – 30	Acute Tox. 4 (Oral), H302 (ATE=1200 mg/kg bodyweight) Eye Irrit. 2, H319 Skin Sens. 1B, H317
Reaction product of 3-aminomethyl-3,5,5-trimethylcyclohexanamine with oligomerisation products of 4,4-propane-2,2-diylldiphenol with 2-(chloromethyl)oxirane	CAS-No.: 38294-64-3 EC-No.: 500-101-4 REACH-no: 01-2119965165-33	15 – 30	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
salicylic acid	CAS-No.: 69-72-7 EC-No.: 200-712-3 EC Index-No.: 607-732-00-5 REACH-no: 01-2119486984-17	< 5	Repr. 2, H361d Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Dam. 1, H318
m-phenylenebis(methylamine)	CAS-No.: 1477-55-0 EC-No.: 216-032-5 REACH-no: 01-2119480150-50	< 5	Acute Tox. 4 (Oral), H302 (ATE=930 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 Skin Corr. 1, H314 Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: General information. Refer to section 11.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	: Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical, CO2, alcohol-resistant foam or waterspray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Carbon monoxide. Other toxic gases.
--	---------------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. See Section 8.
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

6.3. Methods and material for containment and cleaning up

For containment	: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.
-----------------	--

6.4. Reference to other sections

Disposal considerations. See Section 13.

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Storage temperature : < 30 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3, EN ISO 374-1
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Grey.
Appearance	: Liquid high viscosity.
Odour	: Amine-like.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: > 200 °C
Flammability	: Not applicable
Explosive properties	: No data available.
Lower explosion limit	: 1 Vol-%
Upper explosion limit	: Not available
Flash point	: > 100 °C
Auto-ignition temperature	:
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 47619.048 – 100000 mm²/s
Viscosity, dynamic	: 50000 – 90000 mPa·s
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: < 5 hPa
Vapour pressure at 50°C	: Not available
Density	: 0.9 – 1.05 g/cm³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g. by grounding). Protect from sunlight. Avoid high temperatures.

10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met).
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met).

benzyl alcohol (100-51-6)	
LD50 oral rat	1610 mg/kg Source: OECD SIDS
LD50 oral	1580 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1410 - 1770
LD50 dermal rat	2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 4.178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Vapours)	> 4.178 mg/l
salicylic acid (69-72-7)	
LD50 oral rat	891 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 699 - 1140
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 10000 mg/kg Source: International Uniform Chemical Information Database

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

salicylic acid (69-72-7)	
LC50 Inhalation - Rat	> 0.225 mg/kg Source: International Uniform Chemical Information Database
m-phenylenebis(methylamine) (1477-55-0)	
LD50 oral rat	930 mg/kg Source: ECHA
LD50 dermal rat	> 3100 mg/kg bodyweight Animal: rat, Remarks on results: other:
LD50 dermal rabbit	> 3100 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	1.12 mg/l Source: ECHA
Skin corrosion/irritation : Causes severe skin burns.	
salicylic acid (69-72-7)	
pH	2.4 Source: HSDB
Reaction product of 3-aminomethyl-3,5,5-trimethylcyclohexanamine with oligomerisation products of 4,4-propane-2,2-diyldiphenol with 2-(chloromethyl)oxirane (38294-64-3)	
pH	7 Source: ECHA Chem
Serious eye damage/irritation : Causes serious eye damage.	
salicylic acid (69-72-7)	
pH	2.4 Source: HSDB
Reaction product of 3-aminomethyl-3,5,5-trimethylcyclohexanamine with oligomerisation products of 4,4-propane-2,2-diyldiphenol with 2-(chloromethyl)oxirane (38294-64-3)	
pH	7 Source: ECHA Chem
Respiratory or skin sensitisation : May cause an allergic skin reaction.	
Germ cell mutagenicity : Not classified	
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)	
Reproductive toxicity : Suspected of damaging the unborn child.	
STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)	
STOT-repeated exposure : Not classified	
benzyl alcohol (100-51-6)	
NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:
salicylic acid (69-72-7)	
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight Animal: rat
Reaction product of 3-aminomethyl-3,5,5-trimethylcyclohexanamine with oligomerisation products of 4,4-propane-2,2-diyldiphenol with 2-(chloromethyl)oxirane (38294-64-3)	
LOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	10 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)	
MARINEPRO EPOXY PUTTY HARDENER	
Viscosity, kinematic	47619.048 – 100000 mm²/s
benzyl alcohol (100-51-6)	
Viscosity, kinematic	0.005 mm²/s

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met).

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

benzyl alcohol (100-51-6)

LC50 - Fish [1]	460 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	230 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	76828 mg/l Test organisms (species): other:
NOEC chronic fish	48897 mg/l Test organisms (species): other: Duration: '30 d'

salicylic acid (69-72-7)

LC50 - Fish [1]	1370 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	870 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

m-phenylenebis(methylamine) (1477-55-0)

LC50 - Fish [1]	87.6 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	15.2 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	20.3 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	33.3 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	33.3 mg/l Source: EHCA
LOEC (chronic)	15 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	4.7 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

MARINEPRO EPOXY PUTTY HARDENER

Persistence and degradability	Not rapidly degradable
benzyl alcohol (100-51-6)	
Persistence and degradability	Not rapidly degradable

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

salicylic acid (69-72-7)	
Persistence and degradability	Not rapidly degradable
Reaction product of 3-aminomethyl-3,5,5-trimethylcyclohexanamine with oligomerisation products of 4,4-propane-2,2-diylidiphenol with 2-(chloromethyl)oxirane (38294-64-3)	
Persistence and degradability	Not rapidly degradable
m-phenylenebis(methylamine) (1477-55-0)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

benzyl alcohol (100-51-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1
salicylic acid (69-72-7)	
Partition coefficient n-octanol/water (Log Pow)	2.26 Source: National Library of Medicine
Reaction product of 3-aminomethyl-3,5,5-trimethylcyclohexanamine with oligomerisation products of 4,4-propane-2,2-diylidiphenol with 2-(chloromethyl)oxirane (38294-64-3)	
Partition coefficient n-octanol/water (Log Pow)	3.6 Source: ECHA Chem
m-phenylenebis(methylamine) (1477-55-0)	
Partition coefficient n-octanol/water (Log Pow)	0.18

12.4. Mobility in soil

salicylic acid (69-72-7)	
Mobility in soil	23.96 Source: Quantitative Structure Activity Relation
Reaction product of 3-aminomethyl-3,5,5-trimethylcyclohexanamine with oligomerisation products of 4,4-propane-2,2-diylidiphenol with 2-(chloromethyl)oxirane (38294-64-3)	
Mobility in soil	> 398107 Source: ECHA Chem

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains.
Product/Packaging disposal recommendations	: This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
Additional information	: Flammable vapours may accumulate in the container.

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

European List of Waste (LoW, EC 2000/532) : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
15 01 10* - packaging containing residues of or contaminated by dangerous substances
European List of Waste (LoW, EC 2000/532)

SECTION 14: Transport information


In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name		
AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))	AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))	Amines, liquid, corrosive, n.o.s. (m-phenylenebis(methylamine))
Transport document description		
UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)), 8, II, (E)	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)), 8, II, MARINE POLLUTANT	UN 2735 Amines, liquid, corrosive, n.o.s. (m-phenylenebis(methylamine)), 8, II
14.3. Transport hazard class(es)		
8	8	8
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-B	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR) : C7
Limited quantities (ADR) : 1I
Mixed packing provisions (ADR) : MP15
Transport category (ADR) : 2
Orange plates :



Tunnel restriction code (ADR) : E
EAC code : 2X

Transport by sea

Special provisions (IMDG) : 274
Limited quantities (IMDG) : 1 L
Stowage category (IMDG) : A
Segregation (IMDG) : SGG18, SG35

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SECTION 8. SECTION 12.

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
-----	---

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Data sources

: ECHA (European Chemicals Agency).

Training advice

: Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4

MARINEPRO EPOXY PUTTY HARDENER

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1A	H317	Expert judgement
Repr. 2	H361d	Expert judgement
Aquatic Chronic 3	H412	Expert judgement

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.