

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 5/10/2018 Revision date: 1/2/2023 Version: 2.00

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : Spray Filler
Trade name : MULTISPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use

Use of the substance/mixture : The product is intended for professional use

1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o. Żabikowska 7/9

62-052 KOMORNIKI, Poland

Poland

T +48618109800, F +48618109809 sekretariat@novol.com, www.novol.com

E-mail address of competent person responsible for the SDS: dokumentacja@novol.com

1.4. Emergency telephone number

Emergency number : 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Reproductive toxicity, Category 2 H361d
Specific target organ toxicity – Repeated exposure, Category 1 H372

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

GHS08

Signal word (CLP) : Danger Contains : styrene

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H315 - Causes skin irritation. H319 - Causes serious eye irritation.

H361d - Suspected of damaging the unborn child.

H372 - Causes damage to organs (hearing organs) through prolonged or repeated

exposure.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

P260 - Do not breathe vapours, spray.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P312 - Call doctor if you feel unwell.

P271 - Use only outdoors or in a well-ventilated area.

EUH-statements : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3. Other hazards

Other hazards which do not result in classification

: Vapour could form explosive mixture with air. Vapours are heavier than air and spread above ground. Hazardous polymerization may occur if exposed to high temperature.

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene substance with national workplace exposure limit(s) (GB) (Note D)	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0 REACH-no: 01-2119457861- 32	5 – 25	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT RE 1, H372
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] substance with national workplace exposure limit(s) (GB) (Note V)(Note W)(Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379- 17	< 15	Carc. 2, H351
ethyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-	< 13	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium

dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 μm.

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market

in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the

words 'non-stabilised'.

Note V: If the substance is to be placed on the market as fibres (with diameter $< 3 \mu m$, length $> 5 \mu m$ and aspect ratio $\ge 3:1$) or particles

of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or

additional routes of exposure (oral or dermal) should be applied.

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading

to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the

substance; it does not constitute a criterion for classification according to this Regulation.

Full text of H- and EUH-statements: see section 16

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : General information. Refer to section 11.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash

immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse

immediately with plenty of water and seek medical advice.

First-aid measures after ingestion : If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Vapours may cause drowsiness and dizziness.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO2, alcohol-resistant foam or waterspray.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon monoxide. Other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct

or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal

protective equipment as required. See Section 8.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically

recover the product.

1/2/2023 (Revision date) GB - en 3/14

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

6.4. Reference to other sections

Disposal considerations. See Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking. Use only outdoors or in a well-

ventilated area. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be

allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

styrene (100-42-5)			
United Kingdom - Occupational Exposure Limits	United Kingdom - Occupational Exposure Limits		
Local name	Styrene		
WEL TWA (OEL TWA)	430 mg/m³		
	100 ppm		
WEL STEL (OEL STEL)	1080 mg/m³		
	250 ppm		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)		
United Kingdom - Occupational Exposure Limits			
Local name	Titanium dioxide		
WEL TWA (OEL TWA)	4 mg/m³ respirable 10 mg/m³ total inhalable		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
ethyl acetate (141-78-6)			
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Ethyl acetate		
IOEL TWA	734 mg/m³		
	200 ppm		
IOEL STEL	1468 mg/m³		
	400 ppm		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ethyl acetate (141-78-6)	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
United Kingdom - Occupational Exposure Limits	
Local name	Ethyl acetate
WEL TWA (OEL TWA)	734 mg/m³
	200 ppm
WEL STEL (OEL STEL)	1468 mg/m³
	400 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Recommended monitoring procedures

Monitoring methods	
<u> </u>	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

DNEL and PNEC

DNEL and PNEC	
styrene (100-42-5)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	100 mg/m³
Acute - local effects, inhalation	100 mg/m³
Long-term - systemic effects, inhalation	100 mg/m³
Long-term - local effects, inhalation	100 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	10 mg/m³
Acute - local effects, inhalation	10 mg/m³
Long-term - systemic effects,oral	7.7 μg/kg bodyweight/day
Long-term - systemic effects, inhalation	1 mg/m³
Long-term - local effects, inhalation	1 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0.04 mg/l
PNEC aqua (marine water)	0.04 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.418 mg/kg dwt
PNEC sediment (marine water)	0.418 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.146 mg/kg dwt
ethyl acetate (141-78-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1468 mg/m³
Acute - local effects, inhalation	1468 mg/m³
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ethyl acetate (141-78-6)	
ethyl acetate (141-76-6)	
Long-term - systemic effects, inhalation	734 mg/m³
Long-term - local effects, inhalation	734 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	734 mg/m³
Acute - local effects, inhalation	734 mg/m³
Long-term - systemic effects,oral	4.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	367 mg/m³
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day
Long-term - local effects, inhalation	367 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0.24 mg/l
PNEC aqua (marine water)	0.024 mg/l
PNEC aqua (intermittent, freshwater)	1.65 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1.15 mg/kg dwt
PNEC sediment (marine water)	0.115 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.148 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.2 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	650 mg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment symbol(s):







Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : light green.

Appearance : Liquid high viscosity.

Odour : characteristic.

Odour threshold : 0.43 mg/m³ styrene

Melting point : Not applicable

Freezing point : Not available

Boiling point : 77 °C

Flammability : Not applicable

Explosive properties : No data available.

Lower explosion limit : 1.1 vol % styrene

Upper explosion limit : 8 vol % styrene

Flash point : -4 °C ethylacetate

Auto-ignition temperature : 460 °C Decomposition temperature : Not available : Not available Viscosity, kinematic : Not available Viscosity, dynamic 300 - 400 mPa·s Solubility : Slightly soluble. Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : 7.3 hPa styrene Vapour pressure at 50°C : Not available Density : 1.4 g/cm³ Relative density : Not available Relative vapour density at 20°C : Not available Relative density of saturated gas/air mixture : 3.6 styrene

9.2. Other information

Particle characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

: Not applicable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Can react violently with alkalis, as well as a lot of organic products such as alcohols and amines. Hazardous polymerization may occur if exposed to high temperature.

10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g, by grounding). Protect from sunlight. Avoid high temperatures.

10.5. Incompatible materials

Skin corrosion/irritation

No contact with: strong acids, strong bases and strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon monoxide. Other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

styrene (100-42-5)	
LD50 oral rat	5000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.8 mg/l Source: ECHA
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA
ethyl acetate (141-78-6)	
LD50 oral rat	11.3 ml/kg Source: ECHA
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
рН	7 Source: ECHA

: Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Ochous cyc damage/imtation	. Oddses schods eye imation.
titanium dioxide; [in powder form	containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
рН	7 Source: ECHA
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met).
styrene (100-42-5)	
IARC group	2B - Possibly carcinogenic to humans

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met)
ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs (hearing organs) through prolonged or repeated exposure.
styrene (100-42-5)	
STOT-repeated exposure	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term

(chronic)

(acute) Hazardous to the aquatic environment, long-term

: Not classified (Based on available data, the classification criteria are not met)

: Not classified (Based on available data, the classification criteria are not met)

styrene (100-42-5) LC50 - Fish [1] 10 mg/l Source: ECHA EC50 - Crustacea [1] 4.7 mg/l Source: ECHA

EC50 72h - Algae [1] 4.9 mg/l Source: ECHA titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)

LC50 - Fish [1] > 100 mg/lEC50 72h - Algae [1] > 50 mg/l Source: ECHA

ethyl acetate (141-78-6)

LC50 - Fish [1]	230 mg/l Source: ECHA
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

MULTISPRAY	
Persistence and degradability	Not rapidly degradable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

styrene (100-42-5)		
Persistence and degradability	Not rapidly degradable	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)		
Persistence and degradability	Not rapidly degradable	
ethyl acetate (141-78-6)		
Persistence and degradability	Not rapidly degradable	

12.3. Bioaccumulative potential

styrene (100-42-5)		
Partition coefficient n-octanol/water (Log Pow) 2.95 Source: HSDB,CHemIDplus		
ethyl acetate (141-78-6)		
ethyl acetate (141-78-6)		

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

European List of Waste (LoW, EC 2000/532)

- : Disposal must be done according to official regulations.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Do not discharge into drains.
- This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
- : Flammable vapours may accumulate in the container.
- 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

15 01 10* - packaging containing residues of or contaminated by dangerous substances European List of Waste (LoW, EC 2000/532)

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1263	UN 1263	UN 1263

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA		
14.2. UN proper shipping name				
PAINT	PAINT	Paint		
Transport document description				
UN 1263 PAINT, 3, II, (D/E)	UN 1263 PAINT, 3, II (-4°C c.c.)	UN 1263 Paint, 3, II		
14.3. Transport hazard class(es)				
3	3	3		
3	3	3		
14.4. Packing group				
II	II	II		
14.5. Environmental hazards	14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: No		
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 5l
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Transport category (ADR) : 2

Orange plates

33 1263

Tunnel restriction code (ADR) : D/E EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 163, 367
Limited quantities (IMDG) : 5 L
Special packing provisions (IMDG) : PP1
Stowage category (IMDG) : B

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:		
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disruptor	

Data sources : ECHA (European Chemicals Agency).

Training advice : Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Carc. 2	Carcinogenicity, Category 2	
EUH066	Repeated exposure may cause skin dryness or cracking.	
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Repr. 2	H361d	Expert judgement
STOT RE 1	H372	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.