

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Name : Air dry clearcoat HS
Trade name : DART CLEAR 8500

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : The product is intended for professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o.

Żabikowska 7/9

62-052 KOMORNIKI

Poland

T 0048618109800 - F 0048618109809

www.novol.com

E-mail address of competent person responsible for the SDS : dokumentacja@novol.com

1.4. Emergency telephone number

Emergency number : 112

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Danger

Contains :

isobutyl methyl ketone

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Precautionary statements (CLP)	H336 - May cause drowsiness or dizziness. H351 - Suspected of causing cancer. H412 - Harmful to aquatic life with long lasting effects. : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P312 - Call doctor if you feel unwell.
--------------------------------	---

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	20 – 40	Flam. Liq. 3, H226 STOT SE 3, H336
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	5 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
acetone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
methyl acetate substance with national workplace exposure limit(s) (GB)	CAS-No.: 79-20-9 EC-No.: 201-185-2 EC Index-No.: 607-021-00-X REACH-no: 01-2119459211-47	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
isobutyl methyl ketone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-10-1 EC-No.: 203-550-1 EC Index-No.: 606-004-00-4 REACH-no: 01-2119473980-30	5 – 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336
acetic acid 20 % substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note B)	CAS-No.: 64-19-7 EC-No.: 200-580-7 EC Index-No.: 607-002-00-6 REACH-no: 01-2119475328-30	1 – 3	Flam. Liq. 3, H226 Skin Corr. 1A, H314

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS-No.: 104810-48-2+104810-47-1+ 25322-68-3 EC-No.: 400-830-7 EC Index-No.: 607-176-00-3 REACH-no: 01-2119472279-28	≤ 1	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	CAS-No.: 41556-26-7 EC-No.: 255-437-1	< 0.3	Skin Sens. 1, H317 Aquatic Chronic 1, H410 (M=10)
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] (Note P)	CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4 REACH-no: 01-2119486773-24	< 0.2	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)]stannane	CAS-No.: 77-58-7 EC-No.: 201-039-8 EC Index-No.: 050-030-00-3 REACH-no: 01-2119496068-27	< 0.13	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360FD STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Specific concentration limits:

Name	Product identifier	Specific concentration limits
acetic acid 20 %	CAS-No.: 64-19-7 EC-No.: 200-580-7 EC Index-No.: 607-002-00-6 REACH-no: 01-2119475328-30	(10 \leq C < 25) Skin Irrit. 2, H315 (10 \leq C < 25) Eye Irrit. 2, H319 (25 \leq C < 90) Skin Corr. 1B, H314 (90 \leq C \leq 100) Skin Corr. 1A, H314

Note B : Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P : The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: General information. Refer to section 11.

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	: Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact	: May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical, CO ₂ , alcohol-resistant foam or waterspray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Carbon monoxide. Other toxic gases.
--	---------------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. See Section 8.
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

6.3. Methods and material for containment and cleaning up

For containment	: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.
-----------------	--

6.4. Reference to other sections

Disposal considerations. See Section 13.

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m ³ o-,m-,p- or mixed isomers
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m ³
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m ³
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
methyl acetate (79-20-9)	
United Kingdom - Occupational Exposure Limits	
Local name	Methyl acetate
WEL TWA (OEL TWA) [1]	616 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	770 mg/m ³
WEL STEL (OEL STEL) [ppm]	250 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
acetic acid 20 % (64-19-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetic acid
IOEL TWA	25 mg/m ³
IOEL TWA [ppm]	10 ppm

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

acetic acid 20 % (64-19-7)	
IOEL STEL	50 mg/m ³
IOEL STEL [ppm]	20 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
United Kingdom - Occupational Exposure Limits	
Local name	Acetic acid
WEL TWA (OEL TWA) [1]	25 mg/m ³
WEL TWA (OEL TWA) [2]	10 ppm
WEL STEL (OEL STEL)	50 mg/m ³
WEL STEL (OEL STEL) [ppm]	20 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
isobutyl methyl ketone (108-10-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	4-Methylpentan-2-one
IOEL TWA [ppm]	20 ppm
IOEL STEL	208 mg/m ³
IOEL STEL [ppm]	50 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	4-Methylpentan-2-one
WEL TWA (OEL TWA) [1]	208 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	4-methylpentan-2-one
BMGV	20 µmol/l Parameter: 4-methylpentan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

8.1.3. Air contaminants formed

No additional information available

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.1.4. DNEL and PNEC

xylene (1330-20-7)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	289 mg/m ³
Acute - local effects, inhalation	289 mg/m ³
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	77 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	174 mg/m ³
Acute - local effects, inhalation	174 mg/m ³
Long-term - systemic effects, oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.8 mg/m ³
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	12.46 mg/kg dwt
PNEC sediment (marine water)	12.46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.31 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	6.58 mg/l
n-butyl acetate (123-86-4)	
PNEC (Water)	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35.6 mg/l
acetone (67-64-1)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	2420 mg/m ³
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

acetone (67-64-1)	
Long-term - systemic effects, inhalation	1210 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	62 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	200 mg/m ³
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	10.6 mg/l
PNEC aqua (marine water)	1.06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	30.4 mg/kg dwt
PNEC sediment (marine water)	3.04 mg/kg dwt
PNEC (Soil)	
PNEC soil	29.5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
methyl acetate (79-20-9)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	3777 mg/m ³
Long-term - systemic effects, dermal	43 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	300 mg/m ³
Long-term - local effects, inhalation	620 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	203 mg/kg bodyweight/day
Acute - systemic effects, inhalation	3777 mg/m ³
Acute - systemic effects, oral	203 mg/kg bodyweight/day
Long-term - systemic effects, oral	21.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	64 mg/m ³
Long-term - systemic effects, dermal	21.5 mg/kg bodyweight/day
Long-term - local effects, inhalation	133 mg/m ³
acetic acid 20 % (64-19-7)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	25 mg/m ³
Long-term - local effects, inhalation	25 mg/m ³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	25 mg/m ³
Long-term - local effects, inhalation	25 mg/m ³

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

acetic acid 20 % (64-19-7)	
PNEC (Water)	
PNEC aqua (freshwater)	3058 mg/l
PNEC aqua (marine water)	0.3058 mg/l
PNEC aqua (intermittent, freshwater)	30.58 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	11.36 mg/kg dwt
PNEC sediment (marine water)	1136 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.47 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	85 mg/l
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	2.08 mg/kg bodyweight/day
Acute - systemic effects, inhalation	0.059 mg/m ³
Long-term - systemic effects, dermal	0.43 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.02 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	0.5 mg/kg bodyweight/day
Acute - systemic effects, inhalation	0.04 mg/m ³
Acute - systemic effects, oral	0.02 mg/kg bodyweight/day
Long-term - systemic effects, oral	0.0031 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.0046 mg/m ³
Long-term - systemic effects, dermal	0.16 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.000463 mg/l
PNEC aqua (marine water)	0.0000463 mg/l
PNEC aqua (intermittent, freshwater)	0.00463 mg/l
PNEC aqua (intermittent, marine water)	0.00463 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.05 mg/kg dwt
PNEC sediment (marine water)	0.005 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0407 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.2 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

isobutyl methyl ketone (108-10-1)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	208 mg/m ³
Acute - local effects, inhalation	208 mg/m ³
Long-term - systemic effects, dermal	11.8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	83 mg/m ³
Long-term - local effects, inhalation	83 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	155.2 mg/m ³
Acute - local effects, inhalation	155.2 mg/m ³
Long-term - systemic effects, oral	4.2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.7 mg/m ³
Long-term - systemic effects, dermal	4.2 mg/kg bodyweight/day
Long-term - local effects, inhalation	14.7 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.6 mg/l
PNEC aqua (marine water)	0.06 mg/l
PNEC aqua (intermittent, freshwater)	1.5 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	8.27 mg/kg dwt
PNEC sediment (marine water)	0.83 mg/kg dwt
PNEC (Soil)	
PNEC soil	1.3 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	27.5 mg/l
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] (64742-95-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1286.4 mg/m ³
Acute - local effects, inhalation	1066.67 mg/m ³
Long-term - local effects, inhalation	837.5 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	1152 mg/m ³
Acute - local effects, inhalation	640 mg/m ³
Long-term - local effects, inhalation	178.57 mg/m ³

8.1.5. Control banding

No additional information available

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 55 °C
Flammability	: Not applicable
Explosive properties	: No data available.

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Explosive limits	: Not available
Lower explosion limit	: 1.2 vol % Methylisobutylketone
Upper explosion limit	: 8 vol % Methylisobutylketone
Flash point	: 14 °C
Auto-ignition temperature	: ≈ 450 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 21 hPa
Vapour pressure at 50°C	: Not available
Density	: 1 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g. by grounding). Protect from sunlight. Avoid high temperatures.

10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg rat
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

xylene (1330-20-7)	
LC50 Inhalation - Rat	27124 mg/l
n-butyl acetate (123-86-4)	
LD50 oral rat	12.2 ml/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 4.9 mg/l Source: ECHA
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
acetic acid 20 % (64-19-7)	
LD50 oral rat	3310 mg/kg bodyweight Animal: rat, Remarks on results: other:
LD50 oral	4960 mg/kg bodyweight Animal: mouse, Remarks on results: other:
LD50 dermal rabbit	1060 mg/kg Source: HSDB, NITE
LC50 Inhalation - Rat [ppm]	16000 ppm Source: ChemIDPlus
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
LD50 oral rat	2369 – 3920 mg/kg Source: International Uniform Chemical Information Database
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
LD50 oral rat	2071 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:, 95% CL: 1207 - 5106
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 2000 mg/kg
isobutyl methyl ketone (108-10-1)	
LD50 oral rat	2080 mg/kg Source: ECHA
LD50 dermal rabbit	≥ 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	11.6 mg/l Source: ECHA
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] (64742-95-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	5.16 mg/l Source: ECHA

Skin corrosion/irritation : Causes skin irritation.

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

n-butyl acetate (123-86-4)	
pH	6.2 Temp.: 20 °C Concentration: 5,3 g/L
acetic acid 20 % (64-19-7)	
pH	2.4 Source: ECHA
Serious eye damage/irritation	: Causes serious eye irritation.
n-butyl acetate (123-86-4)	
pH	6.2 Temp.: 20 °C Concentration: 5,3 g/L
acetic acid 20 % (64-19-7)	
pH	2.4 Source: ECHA
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Suspected of causing cancer.
isobutyl methyl ketone (108-10-1)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
methyl acetate (79-20-9)	
STOT-single exposure	May cause drowsiness or dizziness.
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
STOT-single exposure	Causes damage to organs.
isobutyl methyl ketone (108-10-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)

acetic acid 20 % (64-19-7)	
NOAEL (oral, rat, 90 days)	290 mg/kg bodyweight Animal: rat, Animal sex: male

dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
STOT-repeated exposure	Causes damage to organs (immune system) through prolonged or repeated exposure.

isobutyl methyl ketone (108-10-1)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

n-butyl acetate (123-86-4)	
Viscosity, kinematic	0.83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'

methyl acetate (79-20-9)	
Viscosity, kinematic	0.391 mm ² /s

acetic acid 20 % (64-19-7)	
Viscosity, kinematic	1015.385 mm ² /s

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] (64742-95-6)	
Viscosity, kinematic	< 1 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Not rapidly degradable

xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

xylene (1330-20-7)	
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Source: ECHA
EC50 - Crustacea [1]	44 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l Source: ECHA
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
methyl acetate (79-20-9)	
LC50 - Fish [1]	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
acetic acid 20 % (64-19-7)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	> 300.82 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	> 300.82 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	> 300.82 mg/l Test organisms (species): Skeletonema costatum
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
LC50 - Fish [1]	0.97 mg/l Source: International Uniform Chemical Information Database
EC50 96h - Algae [1]	0.017 mg/l Source: Ecological Structure Activity Relationships
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
LC50 - Fish [1]	21.2 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1.7 – 3.4 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	< 463 µg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

isobutyl methyl ketone (108-10-1)	
LC50 - Fish [1]	> 179 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] (64742-95-6)	
LC50 - Fish [1]	9.22 mg/l Source: IUCLID
EC50 - Crustacea [1]	6.14 mg/l Source: IUCLID
EC50 72h - Algae [1]	19 mg/l Source: IUCLID

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1.78 Source: HSDB
acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC
methyl acetate (79-20-9)	
Partition coefficient n-octanol/water (Log Pow)	0.18 Source: ICSC
acetic acid 20 % (64-19-7)	
Partition coefficient n-octanol/water (Log Pow)	-0.17 Source: ECHA
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
Partition coefficient n-octanol/water (Log Pow)	0.37 Source: International Uniform Chemical Information Database
dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane (77-58-7)	
Partition coefficient n-octanol/water (Log Pow)	4.44 Source: ECHA
isobutyl methyl ketone (108-10-1)	
Partition coefficient n-octanol/water (Log Pow)	1.31 Source: ChemIDPlus
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] (64742-95-6)	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.7. Other adverse effects

No additional information available




SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains.
Product/Packaging disposal recommendations	: This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
Additional information	: Flammable vapours may accumulate in the container.
European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1866	UN 1866	UN 1866
14.2. UN proper shipping name		
RESIN SOLUTION	RESIN SOLUTION	Resin solution
Transport document description		
UN 1866 RESIN SOLUTION, 3, II, (D/E)	UN 1866 RESIN SOLUTION, 3, II (14°C c.c.)	UN 1866 Resin solution, 3, II
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Transport category (ADR)	: 2

Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Transport by sea

Limited quantities (IMDG) : 5 L
Special packing provisions (IMDG) : PP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): dibutyltin dilaurate (77-58-7)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:	
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : ECHA (European Chemicals Agency).
Training advice : Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H360FD	May damage fertility. May damage the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

DART CLEAR 8500

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
H412	Harmful to aquatic life with long lasting effects.
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Expert judgment

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.