

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Name : ACRYLIC THINNER
Trade name : THIN 80-850 SLOW

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : The product is intended for professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o.

Żabikowska 7/9

62-052 KOMORNIKI

Poland

T 0048618109800 - F 0048618109809

www.novol.com

E-mail address of competent person responsible for the SDS : dokumentacja@novol.com

1.4. Emergency telephone number

Emergency number : 112

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

| | |
|--|------|
| Flammable liquids, Category 3 | H226 |
| Acute toxicity (dermal), Category 4 | H312 |
| Acute toxicity (inhal.), Category 4 | H332 |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336 |


Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



Signal word (CLP) :

Warning

Contains :

n-butyl acetate

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.
H312+H332 - Harmful in contact with skin or if inhaled.
H336 - May cause drowsiness or dizziness.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P261 - Avoid breathing vapours, spray.
P271 - Use only outdoors or in a well-ventilated area.

Precautionary statements (CLP)

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P312 - Call doctor if you feel unwell.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|--|---------|---|
| 2-butoxyethyl acetate; butylglycol acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit | CAS-No.: 112-07-2 EC-No.: 203-933-3 EC Index-No.: 607-038-00-2 REACH-no: 01-2119475112-47 | 35 – 70 | Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 |
| 2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit | CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29 | 20 – 40 | Flam. Liq. 3, H226 |
| n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit | CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29 | 5 – 20 | Flam. Liq. 3, H226 STOT SE 3, H336 |

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures general | : General information. Refer to section 11. |
| First-aid measures after inhalation | : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| First-aid measures after ingestion | : If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : Vapours may cause drowsiness and dizziness. |
| Symptoms/effects after skin contact | : Prolonged or repeated contact may cause skin to become dry. |
| Symptoms/effects after eye contact | : May cause eye irritation. |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO₂, alcohol-resistant foam or waterspray.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon monoxide. Other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.

6.4. Reference to other sections

Disposal considerations. See Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| n-butyl acetate (123-86-4) | |
|--|---|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | n-Butyl acetate |
| IOEL TWA [ppm] | 50 ppm |
| IOEL STEL | 723 mg/m ³ |
| IOEL STEL [ppm] | 150 ppm |
| Regulatory reference | COMMISSION DIRECTIVE (EU) 2019/1831 |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Butyl acetate |
| WEL TWA (OEL TWA) [1] | 724 mg/m ³ |
| WEL TWA (OEL TWA) [2] | 150 ppm |
| WEL STEL (OEL STEL) | 966 mg/m ³ |
| WEL STEL (OEL STEL) [ppm] | 200 ppm |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | 2-Methoxy-1-methylethylacetate |
| IOEL TWA [ppm] | 50 ppm |
| IOEL STEL | 550 mg/m ³ |
| IOEL STEL [ppm] | 100 ppm |
| Remark | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| United Kingdom - Occupational Exposure Limits | |
| Local name | 1-Methoxypropyl acetate |
| WEL TWA (OEL TWA) [1] | 274 mg/m ³ |
| WEL TWA (OEL TWA) [2] | 50 ppm |
| WEL STEL (OEL STEL) | 548 mg/m ³ |
| WEL STEL (OEL STEL) [ppm] | 100 ppm |
| Remark | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| 2-butoxyethyl acetate; butylglycol acetate (112-07-2) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | 2-Butoxyethyl acetate |
| IOEL TWA [ppm] | 20 ppm |
| IOEL STEL | 333 mg/m ³ |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| 2-butoxyethyl acetate; butylglycol acetate (112-07-2) | |
|--|---|
| IOEL STEL [ppm] | 50 ppm |
| Remark | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| United Kingdom - Occupational Exposure Limits | |
| Local name | 2-Butoxyethyl acetate |
| WEL TWA (OEL TWA) [1] | 133 mg/m ³ |
| WEL TWA (OEL TWA) [2] | 20 ppm |
| WEL STEL (OEL STEL) | 332 mg/m ³ |
| WEL STEL (OEL STEL) [ppm] | 50 ppm |
| Remark | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |

8.1.2. Recommended monitoring procedures

| Monitoring methods | |
|---------------------------|---|
| Monitoring methods | EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. |

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

| n-butyl acetate (123-86-4) | |
|---|--------------------------|
| PNEC (Water) | |
| PNEC aqua (freshwater) | 0.18 mg/l |
| PNEC aqua (marine water) | 0.018 mg/l |
| PNEC aqua (intermittent, freshwater) | 0.36 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 0.981 mg/kg dwt |
| PNEC sediment (marine water) | 0.0981 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 0.0903 mg/kg dwt |
| PNEC (STP) | |
| PNEC sewage treatment plant | 35.6 mg/l |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| DNEL/DMEL (Workers) | |
| Acute - local effects, inhalation | 550 mg/m ³ |
| Long-term - systemic effects, dermal | 796 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 275 mg/m ³ |
| DNEL/DMEL (General population) | |
| Long-term - systemic effects, oral | 36 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 33 mg/m ³ |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| 2-methoxy-1-methylethyl acetate (108-65-6) | |
|--|--------------------------|
| Long-term - systemic effects, dermal | 320 mg/kg bodyweight/day |
| Long-term - local effects, inhalation | 33 mg/m ³ |
| PNEC (Water) | |
| PNEC aqua (freshwater) | 0.635 mg/l |
| PNEC aqua (marine water) | 0.0635 mg/l |
| PNEC aqua (intermittent, freshwater) | 6.35 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 3.29 mg/kg dwt |
| PNEC sediment (marine water) | 0.329 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 0.29 mg/kg dwt |
| PNEC (STP) | |
| PNEC sewage treatment plant | 100 mg/l |
| 2-butoxyethyl acetate; butylglycol acetate (112-07-2) | |
| DNEL/DMEL (Workers) | |
| Acute - systemic effects, dermal | 120 mg/kg bodyweight/day |
| Acute - local effects, inhalation | 333 mg/m ³ |
| Long-term - systemic effects, dermal | 169 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 133 mg/m ³ |
| DNEL/DMEL (General population) | |
| Acute - systemic effects, dermal | 72 mg/kg bodyweight/day |
| Acute - systemic effects, oral | 36 mg/kg bodyweight/day |
| Acute - local effects, inhalation | 200 mg/m ³ |
| Long-term - systemic effects, oral | 8.6 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 80 mg/m ³ |
| Long-term - systemic effects, dermal | 102 mg/kg bodyweight/day |
| PNEC (Water) | |
| PNEC aqua (freshwater) | 0.304 mg/l |
| PNEC aqua (marine water) | 0.0304 mg/l |
| PNEC aqua (intermittent, freshwater) | 0.56 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 2.03 mg/kg dwt |
| PNEC sediment (marine water) | 0.203 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 0.415 mg/kg dwt |
| PNEC (Oral) | |
| PNEC oral (secondary poisoning) | 60 mg/kg food |
| PNEC (STP) | |
| PNEC sewage treatment plant | 90 mg/l |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

| Hand protection | | | | | |
|-------------------|----------------------|-------------------|----------------|-------------|----------|
| Type | Material | Permeation | Thickness (mm) | Penetration | Standard |
| Disposable gloves | Viton® II | 6 (> 480 minutes) | 0,7 mm | | EN 374-3 |
| Disposable gloves | Nitrile rubber (NBR) | 2 (> 30 minutes) | 0,4 mm | | EN 374-3 |

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

| Respiratory protection | | | |
|---------------------------|--------------|-----------|----------|
| Device | Filter type | Condition | Standard |
| Gas mask with filter type | Filter A1/B1 | | EN 14387 |

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|------------------------------------|
| Physical state | : Liquid |
| Colour | : Colourless. |
| Odour | : characteristic. |
| Odour threshold | : 0.9 – 9 mg/m ³ Xylene |
| Melting point | : Not applicable |
| Freezing point | : Not available |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| | |
|---|------------------------------|
| Boiling point | : 126 – 140 °C |
| Flammability | : Not applicable |
| Explosive properties | : No data available. |
| Explosive limits | : Not available |
| Lower explosion limit | : 1.1 vol % Xylene |
| Upper explosion limit | : 8 vol % Xylene |
| Flash point | : 24 °C |
| Auto-ignition temperature | : 270 °C |
| Decomposition temperature | : Not available |
| pH | : Not available |
| Viscosity, kinematic | : ≈ 1.111 mm ² /s |
| Viscosity, dynamic | : ≈ 1 mPa.s |
| Solubility | : Slightly soluble. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Vapour pressure | : 13 hPa Butyl acetate |
| Vapour pressure at 50°C | : Not available |
| Density | : ≈ 0.9 g/cm ³ |
| Relative density | : Not available |
| Relative vapour density at 20°C | : Not available |
| Particle characteristics | : Not applicable |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g. by grounding). Protect from sunlight. Avoid high temperatures.

10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

| | |
|-----------------------------|--|
| Acute toxicity (oral) | : Not classified. (Based on available data, the classification criteria are not met) |
| Acute toxicity (dermal) | : Harmful in contact with skin. |
| Acute toxicity (inhalation) | : Harmful if inhaled. |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| THIN 80-850 SLOW | |
|--|--|
| ATE CLP (dermal) | 1571.429 mg/kg bodyweight |
| ATE CLP (gases) | 4500 ppmv/4h |
| ATE CLP (vapours) | 11 mg/l/4h |
| ATE CLP (dust,mist) | 1.5 mg/l/4h |
| n-butyl acetate (123-86-4) | |
| LD50 oral rat | 12.2 ml/kg Source: ECHA |
| LC50 Inhalation - Rat (Vapours) | > 4.9 mg/l Source: ECHA |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| 2-butoxyethyl acetate; butylglycol acetate (112-07-2) | |
| LD50 oral rat | ≈ 1880 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other: |
| LD50 dermal rabbit | ≈ 1500 mg/kg bodyweight Animal: rabbit, Remarks on results: other: |
| LC50 Inhalation - Rat [ppm] | > 400 ppm Source: ECHA |
| Skin corrosion/irritation | : Not classified |
| n-butyl acetate (123-86-4) | |
| pH | 6.2 Temp.: 20 °C Concentration: 5,3 g/L |
| Serious eye damage/irritation | : Not classified (Based on available data, the classification criteria are not met) |
| n-butyl acetate (123-86-4) | |
| pH | 6.2 Temp.: 20 °C Concentration: 5,3 g/L |
| Respiratory or skin sensitisation | : Not classified (Based on available data, the classification criteria are not met) |
| Germ cell mutagenicity | : Not classified (Based on available data, the classification criteria are not met) |
| Carcinogenicity | : Not classified (Based on available data, the classification criteria are not met) |
| Reproductive toxicity | : Not classified (Based on available data, the classification criteria are not met) |
| STOT-single exposure | : May cause drowsiness or dizziness. |
| n-butyl acetate (123-86-4) | |
| STOT-single exposure | May cause drowsiness or dizziness. |
| STOT-repeated exposure | : Not classified (Based on available data, the classification criteria are not met) |
| n-butyl acetate (123-86-4) | |
| LOAEL (oral, rat, 90 days) | 500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents) |
| NOAEL (oral, rat, 90 days) | 125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents) |
| 2-methoxy-1-methylethyl acetate (108-65-6) | |
| NOAEL (oral, rat, 90 days) | ≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| NOAEL (dermal, rat/rabbit, 90 days) | > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| 2-butoxyethyl acetate; butylglycol acetate (112-07-2) | |
|--|---|
| NOAEL (dermal, rat/rabbit, 90 days) | > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

| THIN 80-850 SLOW | |
|-----------------------------------|--|
| Viscosity, kinematic | ≈ 1.111 mm ² /s |
| n-butyl acetate (123-86-4) | |
| Viscosity, kinematic | 0.83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)' |

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Not rapidly degradable

| n-butyl acetate (123-86-4) | |
|------------------------------------|--|
| LC50 - Fish [1] | 18 mg/l Source: ECHA |
| EC50 - Crustacea [1] | 44 mg/l Source: ECHA |
| EC50 - Other aquatic organisms [1] | 32 mg/l Test organisms (species): Artemia salina |
| EC50 72h - Algae [1] | 674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| EC50 72h - Algae [2] | 246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| LOEC (chronic) | 47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | 23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |

| 2-methoxy-1-methylethyl acetate (108-65-6) | |
|---|---|
| LC50 - Fish [1] | > 100 mg/l Test organisms (species): Oryzias latipes |
| EC50 - Crustacea [1] | > 500 mg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | > 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| NOEC (chronic) | ≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic fish | 47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d' |

| 2-butoxyethyl acetate; butylglycol acetate (112-07-2) | |
|--|---|
| LC50 - Fish [1] | 20 – 40 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) |
| EC50 - Crustacea [1] | 37 mg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | 1570 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2] | 520 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2-butoxyethyl acetate; butylglycol acetate (112-07-2)

| | |
|-------------|------------------------|
| ErC50 algae | 1570 mg/l Source: ECHA |
|-------------|------------------------|

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)

| | |
|---|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 1.78 Source: HSDB |
|---|-------------------|

2-butoxyethyl acetate; butylglycol acetate (112-07-2)

| | |
|---|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 1.51 Source: ECHA |
|---|-------------------|

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--|---|
| Regional legislation (waste) | : Disposal must be done according to official regulations. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Sewage disposal recommendations | : Do not discharge into drains. |
| Product/Packaging disposal recommendations | : This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site. |
| Additional information | : Flammable vapours may accumulate in the container. |
| European List of Waste (LoW) code | : 07 01 04* - other organic solvents, washing liquids and mother liquors 15 01 10* - packaging containing residues of or contaminated by dangerous substances |

SECTION 14: Transport information




In accordance with ADR / IMDG / IATA

| ADR | IMDG | IATA |
|---|--|--|
| 14.1. UN number or ID number | | |
| UN 1263 | UN 1263 | UN 1263 |
| 14.2. UN proper shipping name | | |
| PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | Paint related material |
| Transport document description | | |
| UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E) | UN 1263 PAINT RELATED MATERIAL, 3, III (24°C c.c.) | UN 1263 Paint related material, 3, III |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| ADR | IMDG | IATA |
|---|---|---|
| 14.3. Transport hazard class(es) | | |
| 3 | 3 | 3 |
|  |  |  |
| 14.4. Packing group | | |
| III | III | III |
| 14.5. Environmental hazards | | |
| Dangerous for the environment: No | Dangerous for the environment: No Marine pollutant: No | Dangerous for the environment: No |
| No supplementary information available | | |

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 5I
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12

Tunnel restriction code (ADR) : D/E
EAC code : •3Y

Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Special packing provisions (IMDG) : PP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

| Abbreviations and acronyms: | |
|-----------------------------|---|
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BLV | Biological limit value |
| BOD | Biochemical oxygen demand (BOD) |
| COD | Chemical oxygen demand (COD) |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| EC-No. | European Community number |
| EC50 | Median effective concentration |
| EN | European Standard |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median lethal concentration |
| LD50 | Median lethal dose |
| LOAEL | Lowest Observed Adverse Effect Level |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |

THIN 80-850 SLOW

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| Abbreviations and acronyms: | |
|-----------------------------|--|
| OECD | Organisation for Economic Co-operation and Development |
| OEL | Occupational Exposure Limit |
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| ThOD | Theoretical oxygen demand (ThOD) |
| TLM | Median Tolerance Limit |
| VOC | Volatile Organic Compounds |
| CAS-No. | Chemical Abstract Service number |
| N.O.S. | Not Otherwise Specified |
| vPvB | Very Persistent and Very Bioaccumulative |
| ED | Endocrine disrupting properties |

Data sources : ECHA (European Chemicals Agency).
Training advice : Handle in accordance with good industrial hygiene and safety procedures.

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| H226 | Flammable liquid and vapour. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |

| Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]: | | |
|---|------|-----------------------|
| Flam. Liq. 3 | H226 | On basis of test data |
| Acute Tox. 4 (Dermal) | H312 | Expert judgment |
| Acute Tox. 4 (Inhalation) | H332 | Expert judgment |
| STOT SE 3 | H336 | |

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.