




Technical data sheet

Spectral EXTRA 895

Aerosol fade out thinner

PROPERTIES

- aerosol product
- very easy application
- for levelling of optical difference in colour
 - non-irritating smell

USE	
<ul style="list-style-type: none"> coloured acrylic topcoats clearcoat 	
CONTENT OF VOLATILE ORGANIC COMPOUNDS	
VOC II/B/e limit	840 g/l
Actual VOC content	<755 g/l
USAGE INSTRUCTION	
 2min  1-2 coats  5s	<p>Method 1: (recommended): apply the fade out thinner immediately after applying each coating of the clearcoat or topcoat. Apply a thin layer of the product until the spray dust coat has a uniform coating.</p> <p>Application of successive coatings can only be started when Spectral EXTRA 895 evaporates completely</p> <p>Method 2: apply the fade out thinner immediately after applying the last coating of the clearcoat or topcoat. Apply a thin layer of the product until the spray dust forms a uniform coating.</p> <p>CAUTION! Clean the valve after use. Turn the container upside down and spray for about 5 seconds until the valve is empty.</p>
STORAGE CONDITIONS	
<p>Store in a dry and cool room, away from sources of fire and heat.</p> <p>Avoid direct exposure to sunlight.</p>	
SHELF LIFE	
Spectral EXTRA 895	5years/20°C
SAFETY	
See Safety Data Sheet.	
OTHER INFORMATIONS	
<p>Registration number: 000024104.</p> <p>The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.</p>	

