



SMOOTH FOAM

NEUTRAL ACTIVE FOAM

PROPERTIES

pH-neutral active foam for pre-wash, touchless car cleaning. It dissolves oily contamination, road film and all remaining dirt that may cause micro-scratches in the paintwork during hand washing. It is safe for protective coatings and delicate bodywork elements such as trims and seals. It creates a rich, dense, long-lasting foam and has a pleasant fresh raspberry fragrance. Perfect for regular, safe maintenance of the car.

DIRECTIONS FOR USE



1. Do not apply in direct sunlight. Do not apply to hot surfaces.



2. Shake well before use.



3. Dilute to the appropriate ratio:
Foam lance 1:5–1:15
Sprayer 1:20–1:100



4. Apply the foam evenly to the dry bodywork from bottom to top.



5. Leave on the surface for 3–5 minutes, not allowing it to dry.



6. Rinse thoroughly with high-pressure water.

KEY FEATURES

1. Dense, rich foam – effectively softens and removes dirt.
2. Neutral pH – safe for waxes and ceramic coatings.
3. Pleasant fresh raspberry fragrance for more comfortable work.

4. Easy rinsing – no streaks or residues.

STORAGE CONDITIONS



Protect from frost.



Protect from direct sunlight.

OTHER INFORMATION

The effectiveness of our systems is the result of laboratory tests and many years of experience. The data contained in this document are consistent with the current state of knowledge about our products and their possible applications. We guarantee high quality provided that our instructions are followed and the work is carried out in accordance with good trade practice. A trial application is necessary due to potentially different behaviour of the product on various substrates. We do not accept liability if factors beyond our control influenced the final result.

Registration number: 000024104

This Technical Data Sheet supersedes all previous editions.