

**Technical Data Sheet****COBRA WAX & ML****ANTI-CORROSION 2 in 1 UNDERBODY & CAVITY WAX**

<b>PROPERTIES</b>	
COBRA WAX & ML - is a transparent corrosion protection wax with blue UV dye for objects or places where excellent rust preventative surface is needed and to protect closed cavities. The product is free of aromatic solvents and has very good penetration and self-healing properties. Due to the integrated, blue UV additive, with a UV lamp can checked if all areas are correctly coated and protected and helps to control the coating quality over time. After drying remains a slightly sticky wax coating which has a good temperature resistance (from -25°C up to +180°C).	
<b>USE</b>	
The product provides excellent corrosion protection in a wide range of applications, such as: <ul style="list-style-type: none"><li>- Automotive industry;</li><li>- Transportation;</li><li>- Agriculture;</li><li>- Metal industry;</li><li>- Ship constructions;</li><li>- etc.</li></ul>	
<b>SUBSTRATES</b>	
Wide range of substrates	Clean, dry, dust- , rust- and grease-free
It is advisable to carry out an adhesion test with the materials to be used before applying over a large area.	
<b>VOC CONTENT</b>	
VOC II/B/e limit*	840 g/l
Actual VOC	502 g/l
* For ready to apply mixture acc. to EU Directive 2004/42/EC	
<b>APPLICATION</b>	
Airless spraying, pressurised cup gun, conventional gravity-fed spray gun (2,0-2,5mm nozzle), SUPERIOR SPRAY GUN.	
Shake well or stir thoroughly for approx. 2 min before use.	
Recommended air pressure	Instructions of the equipment manufacturer must be followed
Recommended number of layers	2 - 3
Flash off between layers (at 20°C)	2 h
Recommended layer thickness	200µm
<b>APPLICATION CONDITIONS</b>	
It is recommended to apply the product at 15 - 25 °C	
Apply in well ventilated rooms	
Other paint products cannot be applied to the COBRA WAX & ML	



# COBRA WAX & ML

Technical Data Sheet  
10.01.2025

CURING TIMES	
Tack-free	4 h / 20°C
Completely dried	24 h / 20°C
ANTICORROSION	
Minimum 1000 hours, Ri 0 at 100 µm dry layer according to PN-EN ISO 9227 / PN-EN ISO 4628	
COLOUR	
Transparent, yellowish	
EQUIPMENT CLEANING	
THIN 850 acrylic thinner or NC solvent	
STORAGE CONDITIONS	
Store in a cool dry room, away from sources of fire and heat. Avoid direct exposure to sunlight.	
SHELF LIFE	
COBRA WAX & ML	24 months/20°C
SAFETY	
See the Safety Data Sheet.	
OTHER INFORMATION	
Registration number: 000024104.  The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to perform a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.	