



Technical Data Sheet

Date of issue: 30.03.2021

Date of update: 16.04.2021

Version: 2

PREMIUM 110°C MASKING TAPE

Art. No:	91234	19 mm x 50 m
	91235	25 mm x 50 m
	91236	38 mm x 50 m
	91237	50 mm x 50 m

PREMIUM 110°C masking tape is especially engineered for the most demanding automotive spray painting works. The product is resistant to high temperatures applied during spray booth drying cycles as well as IR drying. It leaves no glue residues **up to 30 minutes in 110°C and up to 60 minutes in 90°C**. The tape has excellent adhesion on all surfaces, including plastic and rubber.

Product features:

- High temperature resistant
- Compatible with solventborne paints
- Leaves no glue residues
- Resistant to paint penetration
- Especially designed for the professional user and fitted for most demanding works
- Excellent adhesion to metal, glass, rubber and rough surfaces
- Flexible and efficient

Technical data:

		Test method
Total weight:	92 g/m ²	ISO 536
MD tensile strength:	38 N/cm	AFERA 5004/PSTC 131
MD elongation at break:	7%	AFERA 5004/PSTC 131
Adhesion to steel plate:	2,3 N/cm	AFERA 5001/PSTC 101
Total thickness:	125 µm	
Service temperature up to:	90°C (60 min); 110°C (30 min)	
Backing material:	Saturated crepe paper	
Type of adhesive:	Solvent borne rubber resin	
Tape width:	19 mm; 25 mm; 38 mm; 50 mm	
Tape length:	50 m	

Storage and shelf life:

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. Novol sp. z o.o. does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.