



## Technical Data Sheet

Date of issue: 30.03.2021

Date of update: 30.03.2021

Version: 1

## STANDARD 80°C MASKING TAPE

Art. No:	39215	19 mm x 50 m
	39216	25 mm x 50 m
	39217	30 mm x 50 m
	39218	38 mm x 50 m
	39219	48 mm x 50 m

STANDARD 80°C masking tape is engineered for a professional user. It is suitable for automotive spray painting works. The product is resistant to high temperatures applied during drying cycles in the spray booth (**up to 80 °C resistance for 1 hour**). It has very good adhesion to metal, glass and rubber parts of the car body.

### Product features:

- High temperature resistant (up to 80°C)
- Compatible with solventborne and waterborne paints
- Leaves no glue residues
- Resistant to paint penetration
- Universal use in spray painting, very good adhesion to the car body
- Flexible and efficient

### Technical data:

		Test method
Total weight:	92 g/m <sup>2</sup>	ISO 536
MD tensile strength:	38 N/cm	AFERA 5004/PSTC 131
MD elongation at break:	7%	AFERA 5004/PSTC 131
Adhesion to steel plate:	2,2 N/cm	AFERA 5001/PSTC 101
Total thickness:	120 µm	
Service temperature up to:	80°C (60 min)	
Backing material:	Saturated crepe paper	
Type of adhesive:	Solvent borne rubber resin	
Tape width:	19 mm; 25 mm; 30 mm; 38 mm; 48 mm	
Tape length:	50 m	

### Storage and shelf life:

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. Novol sp. z o.o. does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.