



Technical Data Sheet

Date of issue: 06/12/2021

Date of update: 06/12/2021

Version: 1

UNDERCOATING SPRAY GUN

P/N: 39999 (SAP No. 300000067)

Product overview:

A professional spray gun for application of underbody coatings, car body protection compounds, cavity waxes and sealant products. The self-centring nozzle ensures the correct spray jet width and flow rate adjustment. The pressure die-cast aluminium body is light, ergonomic and robust. The spray gun includes a hose tip for application of cavity waxes.

Characteristics:

- The nozzle adjustment helps with setting the desired texture of applied materials.
- The dedicated hose tip makes application of cavity waxes and anti-rust products convenient.
- Compatible with standard 1-litre threaded-end canisters for underbody coating products and car body protection compounds.
- Light and robust.

Technical data:

	Value
Body material:	Die-cast aluminium
Nozzle port diameter:	Ø 6 mm
Hose tip length:	50 cm
Operating pressure:	3 to 8 bar
Maximum pressure:	10 bar
Compliance:	Machinery Directive 2006/42/WE EN 1953:1998+A1:2009, Atomising and spraying equipment for coating materials — Safety requirements

Shelf life and storage:

The product performs best for 36 months from the production date if stored in its original container, in a dry location between 0°C and +30°C. Keep away from direct heat and sunlight; protect from frost.

Note:

The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to perform a test application of the product due to its potentially different reaction with different materials. We cannot be held liable for defects where the final results were affected by factors beyond our control. NOVOL reserves the right to improve the product and modify the technical requirements, which may entail modification of the specification. This product is not hazardous if used as intended.

NOVOL Sp. z o.o., ul. Żabikowska 7/9, PL62-052 Komorniki, tel. +48 61 810 98 00, novol.com